



1. THIS PLUG IS DESIGNED TO CONFORM TO THE LATEST ISSUE OF MIL-C-24308
 2. MAX WIRE INSUL. TO BE USED WITH THIS PLUG IS .054 DIA.
 3. METAL RETENTION CLIPS ARE INCLUDED IN INSERTS
 4. PACKAGE MARKED M24308/4-269F
 5. THIS PLUG WILL ACCEPT SIZE 22 PIN CONTACT M 39029/58-360 OR ANY AMP HDD-22 PIN CONTACT
- AMP PART NO. MARKED ON CONNECTOR REPRESENTS KIT NUMBER WITH CONTACTS
 UL/CSA DESIGNATION MARKED IN THIS AREA. OPTIONAL

OBSELETE	STEEL, CLASS G	PHENOLIC COLOR: BLACK	204511-3
SUPSD BY 206066-4	BRASS	DIALYL. PHTHALATE COLOR: BLUE	204511-2
	STEEL, CLASS G	DIALYL. PHTHALATE COLOR: BLUE	204511-1
	SHELL MAT'L	INSERT MAT'L	INSERT MAT'L

THIS DRAWING IS A CONTROLLED DOCUMENT

TYSO Electronics Corporation
 Harrisburg, Pa 17105-3608

DRAWING NO: M24308/4-269F
 PROJECT NO: 11-28-78
 DATE: 11-28-78
 DRAWN BY: J.C. BALLER II
 CHECKED BY: J.C. BALLER II
 APPROVED BY: J.C. BALLER II
 SIZE: ONE SIZE (104 POSN) SERIES 90
 PART NO: A100779G=204511
 CUSTOMER DRAWING: YES
 SHEET: 1 OF 1