



1. THIS RCPT. IS DESIGNED TO CONFORM TO THE LATEST ISSUE OF MIL-C-24308
  2. MAX WIRE INSUL. TO BE USED WITH THIS RCPT IS .068 DIA
  3. STAINLESS STEEL RETENTION CLIPS ARE INCLUDED IN INSERTS
  4. PACKAGE STAMPED M2430B/2-293F
  5. THIS RCPT. WILL ACCEPT SIZE 20 SOCKET CONTACT M2430B/10 OR AMP # 205090
- AMP PART NO. STAMPED ON CONNECTOR REPRESENTS KIT NUMBER WITH CONTACTS
- UL/CSA DESIGNATION STAMPED IN THIS AREA.

OBSOLETE	BRASS	205417-2
	STEEL PER ASTM-A-109	205417-1
	SHELL MAT'L	PART NO

DO NOT SCALE PRINT. DIMENSIONS SPECIFIED UNLESS OTHERWISE INDICATED. DIMENSIONS IN INCHES UNLESS OTHERWISE INDICATED. DIMENSIONS IN MILLIMETERS UNLESS OTHERWISE INDICATED. DIMENSIONS IN DECIMALS UNLESS OTHERWISE INDICATED. DIMENSIONS IN FRACTIONS UNLESS OTHERWISE INDICATED. DIMENSIONS IN DECIMALS UNLESS OTHERWISE INDICATED. DIMENSIONS IN FRACTIONS UNLESS OTHERWISE INDICATED.	BY: 12-9-87 C.C. THOMAS	DATE: 12-10-87	PC BALLEW III
DESIGNED BY: C.C. THOMAS	CHECKED BY: PC BALLEW III	DATE: 12-10-87	PC BALLEW III
DRAWN BY: C.C. THOMAS	DATE: 12-10-87	DATE: 12-10-87	PC BALLEW III
MATERIAL: SEE CALLOUTS	PRODUCT SPEC: -	APPLICATION SPEC: -	FINISH: SEE CALLOUTS
WEIGHT: -	SCALE: 4:1	SHEET: 1 OF 1	DRAWING NO: 205417

CUSTOMER DRAWING