



1. THIS PLUG IS DESIGNED TO CONFORM TO THE LATEST ISSUE OF MIL-C-24308
  2. MAX WIRE INSUL. TO BE USED WITH THIS PLUG IS .054 DIA.
  3. METAL RETENTION CLIPS ARE INCLUDED IN INSERTS
  4. PACKAGE MARKED M 24308/4-334F
  5. THIS PLUG WILL ACCEPT SIZE 22 PIN CONTACT M 24308/13 OR AMP # 204370
- AMP PART NO. MARKED ON CONNECTOR REPRESENTS KIT NUMBER WITH CONTACTS

OBSOLETE	PHENOLIC COLOR: BLACK	204535-3
	DIALYL PHTHALATE COLOR: BLUE	204535-1
	INSERT MAT'L	PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.		12-9-87	YAES	YAES Electronics Corporation
DESIGNER	APPROVED	DATE	BY	LOCATION
W. J. THOMAS	J. C. BALLEW II	1-28-88	J. C. BALLEW II	Harrisburg, PA 17105-3608
DESCRIPTION	PROJECT NO.	REV.	DATE	BY
AMPLIMITE PLUG FOR PIN CONTACTS				
SIZE 6, 104 POSN. SERIES 90 WITH FLOAT BUSHINGS				
REVISIONS	REVISIONS	DATE	BY	REVISIONS
1	1	00779	Q=204535	
CUSTOMER DRAWING				