



1. THIS RCPT. IS DESIGNED TO CONFORM TO THE LATEST ISSUE OF MIL-C-24308
 2. MAX WIRE INSUL TO BE USED WITH THIS RCPT IS .054 DIA
 3. METAL RETENTION CLIPS ARE INCLUDED IN INSERTS
 4. PACKAGE MARKED M 24308/2-301F
 5. THIS RCPT. WILL ACCEPT SIZE 22 SOCKET CONTACT M 24308/12 OR AMP # 204351
- △ AMP PART NO. MARKED ON CONNECTOR REPRESENTS KIT NUMBER WITH CONTACTS
 △ UL/CSA DESIGNATION MARKED IN THIS AREA, OPTIONAL

OBSOLETE	PHENOLIC COLOR: BLACK	204532-2
	DIALYL PHTHALATE COLOR: BLUE	204532-1
	INSERT MAT'L	PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT. DATE: 12-4-81

DESIGNER: J.C. THOMAS	DATE: 1-28-78	BY: J.C. THOMAS
CHECKED: E.C. BALLEW	DATE: 1-28-78	BY: E.C. BALLEW
APPROVED: J.C. THOMAS	DATE: 1-28-78	BY: J.C. THOMAS

THIS DRAWING IS A CONTROLLED DOCUMENT. DATE: 12-4-81
 TYS Electronics Corporation
 Harrisburg, PA 17102-2608
 AMPLIMITE RCPT. FOR SOCKET CONTACTS
 HI DENSITY D CONNECTOR, SIZE S, 78 POSN., SERIES 50 WITH FLOAT BUSHINGS.
 SEE ONE ONLY DRAWING NO. A1 00779(G)=204532
 CUSTOMER DRAWING
 SHEET 4:1 OF 1 M