



1. THIS PLUG WILL MATE WITH ANY SIZE 2,26 POSN. RECEPTACLE IN AMPLIMITE SERIES.
2. MAXIMUM WIRE INSULATION TO BE USED WITH THIS PLUG IS .054 DIA.
3. SST RETENTION CLIPS ARE INCLUDED IN INSERTS.
4. THIS PLUG IS DESIGNED TO CONFORM TO THE LATEST ISSUE OF MIL-C-24308.
5. CONNECTOR SUPPLIED WITHOUT CONTACTS SHOWN FOR ILLUSTRATION ONLY.
6. THIS PLUG WILL ACCEPT SIZE 22 DM PIN CONTACT M39029/58-22-22D OR ANY AMP SIZE 22 DF PIN CONTACT.

▲ UL/CSA DESIGNATION STAMPED IN THIS AREA

AS SHOWN	445010-1
DESCRIPTION	PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.		DATE: 10-17-88	BY: [Signature]	REVISED BY: [Signature]	DATE: 10-17-88
DESIGNER: [Signature]	APPROVED: [Signature]	DATE: 10-17-88	BY: [Signature]	REVISED BY: [Signature]	DATE: 10-17-88
PROJECT: [Signature]	DATE: 10-17-88	BY: [Signature]	REVISED BY: [Signature]	DATE: 10-17-88	
DESCRIPTION: [Signature]	DATE: 10-17-88	BY: [Signature]	REVISED BY: [Signature]	DATE: 10-17-88	
SIZE: A1	DATE: 10-17-88	BY: [Signature]	REVISED BY: [Signature]	DATE: 10-17-88	
SIZE: 1:1	DATE: 10-17-88	BY: [Signature]	REVISED BY: [Signature]	DATE: 10-17-88	
SIZE: 1:1	DATE: 10-17-88	BY: [Signature]	REVISED BY: [Signature]	DATE: 10-17-88	