



- CONTACTS: PHOSPHOR BRONZE; HOUSING & PIN SPACER: UL 94V-0 RATED, THERMOPLASTIC, BLACK; BRACKET: ZINC; SHELL: CARBON STEEL; BOARDLOCKS: COPPER ALLOY.
- 0.76µm [(.000030)] MIN GOLD FOR A LENGTH OF 0.64 [(.025)] MAX, 0.13 [(.005)] MIN FROM MATING END, 3.81µm [(.00150)] MIN TIN-LEAD ON OPPOSITE END FOR A LENGTH OF 2.72 [(.107)] MIN, BOTH OVER 1.27µm [(.00050)] MIN NICKEL.
- SHELL: 5.08µm [(.000200)] MIN NICKEL OVER 1.27µm [(.00050)] MIN COPPER.
- BRACKET: 2.54µm [(.000100)] MIN NICKEL OVER 5.08µm [(.000200)] COPPER.
- BOARDLOCK: 5.08µm [(.000200)] MIN TIN-LEAD OVER 1.27µm [(.00050)] MIN NICKEL.

57.91 [2.280]	0.64 [(.025)]	49.12 [1.934]	61.72 [2.430]	63.88 [2.515]	46.13 [1.816]	57.91 [2.280]	68	787525-7																
40.13 [1.580]	0.64 [(.025)]	36.78 [1.448]	43.56 [1.715]	46.10 [1.815]	28.35 [1.116]	40.13 [1.580]	40	787525-4																
L	G	F	E	D	B	A	NO OF POSN	PART NUMBER																
<table border="1"> <tr> <td>MINIMUM TYPICAL DIMENSIONS</td> <td>NO. OF LEADS</td> <td>SHIELD</td> <td>AMP Incorporated Harrisburg, PA 17105-3608</td> </tr> <tr> <td>MINIMUM TYPICAL DIMENSIONS</td> <td>NO. OF POSN</td> <td>RECEPTACLE</td> <td>RECEPTACLE ASSEMBLY, SHIELDED, RIGHT ANGLE, 050 SERIES, AMPLITEM™</td> </tr> <tr> <td>MINIMUM TYPICAL DIMENSIONS</td> <td>NO. OF HOLES</td> <td>PCB THICKNESS</td> <td>114-40029</td> </tr> <tr> <td>MINIMUM TYPICAL DIMENSIONS</td> <td>NO. OF HOLES</td> <td>PCB THICKNESS</td> <td>114-40029</td> </tr> </table>									MINIMUM TYPICAL DIMENSIONS	NO. OF LEADS	SHIELD	AMP Incorporated Harrisburg, PA 17105-3608	MINIMUM TYPICAL DIMENSIONS	NO. OF POSN	RECEPTACLE	RECEPTACLE ASSEMBLY, SHIELDED, RIGHT ANGLE, 050 SERIES, AMPLITEM™	MINIMUM TYPICAL DIMENSIONS	NO. OF HOLES	PCB THICKNESS	114-40029	MINIMUM TYPICAL DIMENSIONS	NO. OF HOLES	PCB THICKNESS	114-40029
MINIMUM TYPICAL DIMENSIONS	NO. OF LEADS	SHIELD	AMP Incorporated Harrisburg, PA 17105-3608																					
MINIMUM TYPICAL DIMENSIONS	NO. OF POSN	RECEPTACLE	RECEPTACLE ASSEMBLY, SHIELDED, RIGHT ANGLE, 050 SERIES, AMPLITEM™																					
MINIMUM TYPICAL DIMENSIONS	NO. OF HOLES	PCB THICKNESS	114-40029																					
MINIMUM TYPICAL DIMENSIONS	NO. OF HOLES	PCB THICKNESS	114-40029																					
CUSTOMER DRAWING							Alt 100779	787525	REV 4.1															