



#### General ordering data

Order No.	1665070000
Part designation	HDC 16A SLU 2PG16G
Version	HDC enclosures, Size: 5, IP 65 / IP 66, Base, longitudinal locking, standard
EAN	4008190421779
Qty.	1 pc(s).

#### Dimensions

Total length	79 mm
Width housing C	29.5 mm
Width base C1	50 mm
Height of housing B	57 mm
Height of base B1	4 mm
Mounting hole distance, width C2	40 mm
Hole pitch length A2	64 mm
Cable entry	PG 16

#### General data

Protection class	IP 65 / IP 66
Housing main material	diecast aluminium
Colour	grey
Temperature, min.	-40 °C
Temperature, max.	125 °C

#### Version

Type of housing	Base housing
Cable entry	w. threading
Number of cable entry on top	0
Number of cable entry sideways	2
Cover	without cover
Cover	without cover
Size	5
Design	standard
Upper part/Lower part/Cover	Lower part

#### Version

locking system	End-locking clamp, lower side
Cable entry	PG 16

#### Approvals

Approvals institutes



#### Downloads

EPLAN	1665070000.MZF
PDF	PDF/1665070000_HDC_16A_SLU_2PG16G_STP_Blatt__1.pdf
DXF	1665070000_HDC_16A_SLU_2PG16G_STP.dxf
IGES	1665070000_HDC_16A_SLU_2PG16G_STP.igs
STEP	1665070000_HDC_16A_SLU_2PG16G_STP.stp
VRML	1665070000_HDC_16A_SLU_2PG16G_STP.wrl

#### Classifications

ETIM 2.0	EC000437
ETIM 3.0	EC000437
eClass 4.1	27-14-08-05
eClass 5.0	27-14-34-19
eClass 5.1	27-14-34-19

#### Similar products

Order No.	Part designation	Version
1788790000	HDC 16A SDLU 2M20G	HDC enclosures, Size: 5, IP 65 / IP 66, Base, longitudinal locking, standard
1788780000	HDC 16A SDLU 2M25G	HDC enclosures, Size: 5, IP 65 / IP 66, Base, longitudinal locking, standard
1665300000	HDC 16A SDLU 2PG16G	HDC enclosures, Size: 5, IP 65 / IP 66, Base, longitudinal locking, standard
1665090000	HDC 16A SLU 1PG21G	HDC enclosures, Size: 5, IP 65 / IP 66, Base, longitudinal locking, standard
1788770000	HDC 16A SLU 2M20G	HDC enclosures, Size: 5, IP 65 / IP 66, Base, longitudinal locking, standard
1788760000	HDC 16A SLU 2M25G	HDC enclosures, Size: 5, IP 65 / IP 66, Base, longitudinal locking, standard