



- ▲ MATERIAL
 HOUSING: GLASS FILLED HIGH TEMPERATURE NYLON, COLOR: BLACK.
 EXTRACTORS: GLASS FILLED HIGH TEMPERATURE NYLON, COLOR: NATURAL (OFF-WHITE).
 CONTACT: PHOS. BRONZE, C51100, TEMPER H06.
- ▲ FINISH
 CONTACT:
 NICKEL PLATE ALL OVER 0.00127mm - 0.0019mm [0.000050 IN - 0.000075 IN] THICK.
 PER AMP SPEC 112-25-2.
 GOLD PLATE IN INTERFACE AREA 0.00038mm [0.000015 IN] THICK.
 PER AMP SPEC 112-162-5.
 MATTE TIN PLATE IN SOLDER TAIL AREA 0.00038mm - 0.00635mm [0.000150 IN - 0.000250 IN] THICK.
 PER AMP SPEC 112-65-1.
- ▲ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER DRENAUD/D.SINISI

OBsolete	DETAIL-C	DETAIL-C	NON-BUFFERED DRAM, 2.5 VOLT, PRE-PLATED CONTACTS	5390323-3
OBsolete	DETAIL-C	DETAIL-A	NON-BUFFERED DRAM, 3.3 VOLT, PRE-PLATED CONTACTS	5390323-1
	FUNCTION KEY #1	VOLTAGE KEY #2	DESCRIPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT. SEE THE MATRICAL RECORD FOR THE LATEST REVISION.

INCHES (mm INCHES)

UNLESS OTHERWISE SPECIFIED:

FINISH: NICKEL PLATE ALL OVER 0.00127mm - 0.0019mm [0.000050 IN - 0.000075 IN] THICK. PER AMP SPEC 112-25-2. GOLD PLATE IN INTERFACE AREA 0.00038mm [0.000015 IN] THICK. PER AMP SPEC 112-162-5. MATTE TIN PLATE IN SOLDER TAIL AREA 0.00038mm - 0.00635mm [0.000150 IN - 0.000250 IN] THICK. PER AMP SPEC 112-65-1.

DATE: 11/07/05 DRAWING NO: A1007798 REV: 1

CUSTOMER DRAWING: TSS ELECTRONICS CORPORATION, SHANGHAI, 200233

SOCKET ASSEMBLY, DRAM2P, LOW INSERTION FORCE, 100 POSN, LEAD-FREE

SIZE: 1:1 SHEET: 1 OF 2

