



- △ PIN: 0.00076[0.00030] MINIMUM GOLD IN CONTACT AREA, 0.00381[0.00150] MINIMUM TIN ON SOLDER TAILS, ALL OVER 0.00127[0.00050] MINIMUM NICKEL
- 2. CUSTOMER TO PROVIDE CARD GUIDANCE SYSTEM
- △ DATUMS AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER
- 4. CONNECTOR REQUIRES USE OF 2 - SIZE 2M SCREWS FOR FASTENING TO PRINTED CIRCUIT BOARD
- △ ASSEMBLY KEYED FOR 5 VOLT CARDS
- △ ASSEMBLY KEYED FOR LOW VOLT CARDS (3.3V)
- △ MATERIAL: HOUSING & ORGANIZER: LCP, COLOR: BLACK; PIN: BRASS; HOLD-DOWN: PHOSPHOR BRONZE; HOLD-DOWN: TIN PLATED

△	1,17,34	ALL OTHER PINS	36,67	5535660-2										
△	1,17,34	ALL OTHER PINS	36,67	5535660-1										
△	35,51,68	ALL OTHER PINS	36,67	5535660-1										
VOLTAGE KEYING & IDENTIFICATION	5.0	4.25	3.5	PART NO										
	[.197]	[.167]	[.138]											
	"L" (PIN LENGTH) AND LOCATION													
THIS DRAWING IS A CONTROLLED DOCUMENT														
<table border="0"> <tr> <td>DATE</td> <td>BY</td> <td>CHKD</td> <td>APP'D</td> <td>REV</td> </tr> <tr> <td>03-28-05</td> <td>JG</td> <td>GP</td> <td>GP</td> <td>0</td> </tr> </table>					DATE	BY	CHKD	APP'D	REV	03-28-05	JG	GP	GP	0
DATE	BY	CHKD	APP'D	REV										
03-28-05	JG	GP	GP	0										
TYPYCO ELECTRONICS CORPORATION HARRISBURG, PA 17105-3008														
RAISED HT, TOP 80 MFG, THRU-HOLE WITH HOLD-DOWNS, AMP MEMORY CARD														
PART NO: 5535660-2 REV: 0 DATE: 03-28-05 DRAWN BY: JG CHECKED BY: GP APPROVED BY: GP PART WEIGHT: 0.5 GRAMS CUSTOMER DRAWING: NO														

COPYRIGHT 2005 TYCO ELECTRONICS CORP ALL RIGHTS RESERVED