


KEYING OPTIONS  
 SOME DETAIL OMITTED FOR CLARITY



SECTION A-A

△ HOUSING: NYLON MOLDING COMPOUND, BLACK.  
 TERMINALS: 0.0[.012] THICK PHOS BRONZE.  
 PLATING: NICKEL UNDERPLATE OVER ENTIRE TERMINAL. 2.54µm[.000100] MINIMUM THICKNESS.  
 LOCALIZED PLATING AREA: 0.254µm[.000010] THICK GOLD OVER 1.015µm[.000040] MINIMUM THICK PALLADIUM NICKEL (OVER 0.05µm[.000002] MINIMUM THICK GOLD WHEN REQUIRED BY PROCESS CONDITIONS).  
 SOLDERABLE AREA PLATED WITH MATTE TIN 3.81 MICRONS MINIMUM THICK.  
 2. 5558666-1 KEY1 (CLOSED) AS SHOWN.

KEY	PART NUMBER
KEY 5	5558666-5
KEY 4	5558666-4
KEY 3	5558666-3
KEY 2	5558666-2
KEY 1	5558666-1

THIS DRAWING IS A CONTROLLED DOCUMENT		DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION
APPROVED	DESIGNED	19900209	GP	REL. AS PER EC 0013-0313-02	19900209	GP	REL. AS PER EC 0013-0313-02
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION	DATE	BY
19900209	GP	REL. AS PER EC 0013-0313-02	19900209	GP	REL. AS PER EC 0013-0313-02	19900209	GP

DESCRIPTION	CONNECTOR ASSEMBLY, CABLE, 15 POSITION, INFOPORT, SERIES III
DATE	19900209
BY	GP
DESCRIPTION	REL. AS PER EC 0013-0313-02
DATE	19900209
BY	GP
DESCRIPTION	REL. AS PER EC 0013-0313-02
DATE	19900209
BY	GP