



- △ CONTACTS: 0.00076[0.00030] MINIMUM GOLD IN CONTACT AREA, 0.0036[0.00150] MIN TIN ON SOLDER TAILS, ALL OVER 0.0012[0.00050] MINIMUM NICKEL.
- 2. CUSTOMER TO PROVIDE CARD GUIDANCE SYSTEM
- △ DATUMS AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER
- 4. CONNECTOR REQUIRES USE OF 2 - SIZE 2M SCREWS FOR FASTENING TO PRINTED CIRCUIT BOARD
- △ ASSEMBLY KEYED FOR 5 VOLT CARDS
- △ ASSEMBLY KEYED FOR LOW VOLT CARDS (3.3V)
- △ RECESSED AMP AND CSA LOGOS LOCATED ON BOTH SIDES OF HOUSING.
- △ MATERIAL: HOUSING & ORGANIZER; LCP, COLOR; BLACK CONTACTS; BRASS

△	1,17,34	ALL OTHER PINS	36,67	5535653-2
△	35,51,68	OTHER PINS	36,67	5535653-1
△	1,17,34	ALL OTHER PINS	36,67	5535653-1
△	35,51,68	OTHER PINS	36,67	5535653-1
△	5.0	4.25	3.5	PART NUMBER
△	1.197	1.67	1.138	PART NUMBER
△	"L" (PIN LENGTH) AND LOCATION			

THIS DRAWING IS A CONTROLLED DOCUMENT. IN VANDIA - 00000000

DESIGNED BY	DATE	REVISED BY	DATE
APPROVED BY		APPROVED BY	

TE Connectivity

PIN HEADER ASSY, 68 POSN, TOP BOARD MFG, THRU-HOLE, AMP MEMORY CARD

WEIGHT 7.3 GRAMS

DATE 00779

REVISED BY 5535653

CUSTOMER DRAWING

SCALE 4:1

SHEET 1 OF 1

**COPYRIGHT 2005
TE CONNECTIVITY CORP
ALL RIGHTS RESERVED**