



- ▲ 0.00076[0.00030] MINIMUM GOLD IN CONTACT AREA.
 0.00381[0.00150] MIN TIN-LEAD ON SOLDER TAILS.
 ALL OVER 0.00127[0.00050] MINIMUM NICKEL
- 2. CUSTOMER TO PROVIDE CARD GUIDANCE SYSTEM
- ▲ DATUMS AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER
- 4. CONNECTOR REQUIRES USE OF 2 - SIZE 2M SCREWS FOR FASTENING TO PRINTED CIRCUIT BOARD
- ▲ ASSEMBLY KEYED FOR 5 VOLT CARDS
- ▲ ASSEMBLY KEYED FOR LOW VOLT CARDS (3.3V)
- ▲ RECESSED AMP AND CSA LOGOS LOCATED ON BOTH SIDES OF HOUSING.
- ▲ MATERIAL: HOUSING & ORGANIZER: LCP, COLOR: BLACK
 PIN: BRASS

▲	1.17,34 35,51,68	ALL OTHER PINS	36,67	535653-2	
▲	1.17,34 35,51,68	OTHER PINS	36,67	535653-1	
VOLTAGE KEYING & IDENTIFICATION	5,0 [.197]	4,25 [.167]	3,5 [.138]		
"L" (PIN LENGTH) AND LOCATION PART NO.					
THIS DRAWING IS A CONTROLLED DOCUMENT					
STANDARD MATERIAL	AMP AMP AMP AMP	MATERIAL SPEC MATERIAL SPEC MATERIAL SPEC MATERIAL SPEC	DATE DATE DATE DATE	DRAWN BY CHECKED BY APPROVED BY	Title Electronics Corporation Millsboro, PA 17105-9608
PIN HEADER ASSY, 68 POSN, TOP BOARD MFG, THRU-HOLE, AMP MEMORY CARD					
MATERIAL: AMP 7.3 GRAMS A1 00779 C-535653					
CUSTOMER DRAWING REF: 4:1 SHEET 1 OF 1					