



- △ PIN: 0.00076[.000030] MINIMUM GOLD IN CONTACT AREA, 0.00381[.000150] MIN TIN ON SOLDER TAILS, ALL OVER 0.00127[.000050] MINIMUM NICKEL
- △ DATUMS AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER
- 3. CONNECTOR REQUIRES USE OF 4 - SIZE 2M SCREWS FOR FASTENING TO PRINTED CIRCUIT BOARD
- △ RECESSED AMP AND CSA LOGOS LOCATED ON BOTH SIDES OF HOUSINGS.
- △ ASSEMBLY KEYED FOR 5 VOLT CARDS.
- △ ASSEMBLY KEYED FOR LOW VOLT CARDS (3.3V).
- △ MATERIAL: HOUSING, GUIDES, SHROUD, BUTTON & ORGANIZER: LCP, COLOR: BLACK PINS: PHOSPHOR BRONZE & BRASS EJECTOR, RAIL PLATE & LEVER: STAINLESS STEEL
- △ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

8	△ OBSOLETE	1,17,34 35,51,68	ALL OTHER PINS	36,67	-6146029-2
	△	1,17,34 35,51,68	ALL OTHER PINS	36,67	5146029-1
	△	5.0	4.25	3.5	PART NUMBER
	△	[.197]	[.167]	[.138]	"L" (PIN LENGTH) AND LOCATION

THIS DRAWING IS A CONTROLLED DOCUMENT. IN STOCK BY TYCO ELECTRONICS CORPORATION. DATE: 01-10-05. BY: J. COLEBY. REV: 01-10-05.

DESIGNING: []	DATE: []	BY: []	REV: []	APP: []	DATE: []	BY: []	REV: []
TYCO ELECTRONICS CORPORATION				HARRISBURG, PA 17105-3608			
CONNECTOR ASSY, STACKED PIN HEADER				WITH LH EJECTOR, 136 POSN, TOP SD MFG.			
THRU-HOLE AMP MEMORY CARD				REWORKED TO:			
CUSTOMER DRAWING				A1 00779 5146029			
DATE: 4-1				REV: 2 # 2			

**COPYRIGHT 2005
TYCO ELECTRONICS CORP
ALL RIGHTS RESERVED**