

Product change notification

PCN09-3-CCM

Document revision

Revision	Date	Description	Author
A	February 16, 2009	Creation	J. Smolinski
B	February 16, 2009	Modification in Annex 1 of CCM01-2270 description and equivalent in New version	J. Smolinski

Summary

1.	Purpose.....	4
2.	Change definition.....	4
3.	Change impact.....	4
3.1	Coplanarity.....	4
3.2	Insulator resistance.....	5
3.3	Card detect switch sealing to dust.....	6
3.4	Changes.....	6
4.	Application.....	7
4.1	Overview.....	7
4.2	Product range affected.....	7
4.3	Date of application & time frame.....	7
4.4	Ordering, pricing and stock handling policy.....	7
4.5	Customer qualification.....	8
5	Acknowledgement.....	8
6	Support.....	8

1. Purpose

Following the development of new constraint and usage related to the smart card connector in its environment we've released a new generation of CCM01-MK2 (V2) to replace completely the existing products (V1)


2. Change definition

The target of this new product is to improve the robustness of the product but also of its processing:

- Coplanarity
- Insulator resistance
 - Card guide wall resistance to extreme insertion
 - Card stop breakage
- Card detection switch dust sealing


3. Change impact

3.1 Coplanarity



V1 version

Crimped PCF (inserted contacts into a plastic block being crimped on main insulator)



V2 version



Individual contact crimping

3.2 Insulator resistance



To limit insulator being cut at card entry

We removed the lateral chamfer (card guiding weak point): Thickness increase of the card entry wall





Wall resistance moved up to 75N for card wrongly inserted and to 40N for lateral insertion



To limit card stop breakage

Card stop section improvement


- plastic wall thickness from 0.70 to 0.75mm
- support surface increase



Card stop resistance moved up 30% at 335N


3.3 Card detect switch sealing to dust

Replacement of the existing KSC switch in V1 by a new SLP switch in V2, specifically developed for the application




3.4 Changes

No changes have been brought to this new generation of product in term of form factor, global volume, PCB layout, or available space below the connector for extra components. The only mechanical difference is the appearance of 6 little pegs below the insulator:



The pegs are necessary for the optional APS cover protection as shown on the figure below:



4. Application

4.1 Overview

Since products are fully compatible and respect the same specifications, the change over from one version to the new product can be easily done, finishing existing stock in the supply chain and replace it by the new version.

4.2 Product range affected

All CCM01 MK2 except version with 4 clips (see annex 1)

4.3 Date of application & time frame

- Samples availability: available
- Last time buy: June 15th 2009 with deliveries in the following two (2) month
- Discontinuation of old version and application date for new version: July 15th 2009

Note: C&K will apply the change on any P/N prior to the application date in the case of the entire necessary customer approval will be received. The corresponding information will be forwarded on time through our customer service network.

4.4 Ordering, pricing and stock handling policy

- Ordering: P/N codes as per table on annex 1.
- Pricing: any pricing and other sales conditions remain valid.
- Stock handling: no obsolescence and no specification modification is applied on any P/N.
- No return or scrap for obsolescence will be accepted.

C&K components

C&K components SAS - 1 rue Louis de la Verne B.P. 359 F-39105 Dole Cedex - FRANCE
Telephone: +33 (0)3 84 72 94 37 - Facsimile: +33 (0)3 84 79 20 39 – www.ck-components.com

Document subject to change without prior notice
Diffusion: no restriction

4.5 Customer qualification

We recommend to our customers to carry on the necessary actions and qualifications they feel necessary to make sure that they will be ready at the date of application. We haven't modified the product features to minimize the customer impact and make easier the modification acceptance. **For any reason, if you evaluate that your acceptance will be released after the date of application, you have to notify C&K components at least 1 month before the application date, ie May 15th 2009.** Without this notification, the change will be applied on any purchased products affected by the modification.

As no material modification is done, the IMDS data remain unchanged.

5 Acknowledgement

We recommend acknowledging this PCN with your requirements in terms of samples & qualification files no later than March 15th 2009 at the following email address: fabrice.valcher@coactive-tech.com.

6 Support

| For any question, please contact Fabrice Valcher at the above email address


ANNEX 1**OLD VERSION****NEW VERSION**

CCM01-2251 LFT T30/ 8 contacts SMT with 2 locating pegs	CCM01-2013AP LFT T30/
CCM01-2252 LFT T30/ 16 contacts SMT with 2 locating pegs	No replacement
CCM01-2253 LFT T30/ 8 contacts SMT with 2 locating pegs	CCM01-2013AP LFT T30/
CCM01-2254 LFT T30/ 16 contacts SMT with 2 locating pegs	No replacement
CCM01-2255 LFT T30/ 8 contacts through hole with 2 locating pegs	CCM01-2012AP LFT T30/
CCM01-2256 LFT T30/ 16 contacts through hole with 2 locating pegs	No replacement
CCM01-2270 LFT T30/ 8 contacts through hole no brake with 2 locating pegs	CCM01-2112AP LFT T30/ (drawing under revision)


Please note that CCM01-2065 and CCM01-2069 are not discontinued yet.

16 contacts version can be replaced by 8 contacts version.

Drawings and specifications of new version can be found on the next pages.



REV.	N° DCR	NATURE DE LA MODIFICATION	DATE	VISA
B	ECR-1406	References table added ; designation and marking updated	11/09/2007	VP
C	ECR-1922	Part number Y112-2013CPLFT added	25/02/2008	
D	ECR-2182	Designation updated	07/05/2008	CD





SYSTEM CONFIDENTIAL

Packaging	Packaging drawing	Marking	Designation	Part Number
Tray 30 parts	030278Y0043		CCM01-2013AP LFT T30/Y112-2013APLFT	
Tray 25 parts	030278Y0064	2013TP	CCM01-2013CP LFT T25/Y112-2013CPLFT	
Reel	030278Y0059		CCM01-2013BP LFT R201/Y112-2013BPLFT	

Notes :

- 1 - Termination to PCB : SMT reflow soldering Temperature/time profile according to : C&K PS-LF-001 specification. Since there are no boardlocks , the connector must be held in place on the PCB across the top face of the cover.
- 2 - Level of each contact tail compared to the nearest plastic stand-off. Coplanarity of metal soldering surfaces : 0,15 mm
- 3 - Recommendation for solder paste thickness > 0,2 mm.
- 4 - 2,5 microns min tin plating on contact terminal areas. 0,1 microns min gold plating on switch terminal areas.
- 5 - Contact forces :
 - max 0,5 N per contact with max. card thickness.
 - min 0,2 N per contact with min. card thickness.
- 6 - Card end travel switch NO activates when the sliding card is 0,9 mm from the card stop.
- 7 - In case of customer accessories integration requesting an interface with CCM, please ask C&K for a 3D model.




MATIERE	TOL LINEAIRE	± 0,1	TRAITEMENT	TOL ANGULAIRE	± 2 °	PROTECTION	DIMENSIONS CRITIQUE
SAUF INDIQUE :							
-COTES DONNEES AVANT PROTECTION							
BAUVIRES ET ARETES VIVES SUPPRIMEES							
DESSINE	PAILLE V.	03/07/2007	ANALYSE	Y	TAB FAN	Y	PROJE
VERIFIE	PINON G.	07/05/2008	REPLACE				
APPROUVE	KUBAT L.	07/05/2008					
G&K C&K Components		PROJECTION PER DEDRE		DESIGNATION		CCM01-2013xPLFT 2 pegs 3,14 mm	
BP 359 - 39105 Dole - FRANCE -		TAILLE		FEUILLE		NUMERO	
		A3		1 / 1		CU	
						112MIY2013	
						REV D	

LE PLAN EST LA PROPRIETE DE C&K COMPONENTS SAS ET NE DOIT ETRE REPRODUIT OU COMMUNIQUE SANS SON AUTORISATION



A B C D E F

CE PLAN EST LA PROPRIETE DE C&K. COMPOSANTS SAS ET LE PEUT ETRE REPRODUIT OU COMMUNIQUE SANS SON AUTORISATION.



SYSTEM CONFIDENTIAL

RECOMMENDED PC BOARD LAYOUT
(Component side)

MATIERE	TRAITEMENT	PROTECTION
SANS INDIQUE	TOL. LINEAIRE ± 0,1	TOL. ANGULAIRE ± 2
COTES DONNEES AVANT PROTECTION	ETAT DE SURFACE Ra	DIMENSIONS CRITIQUES
SAVURES ET ARETES VIVES SUPPRIMEES		DIMENSIONS SPC
DESINE P.DAUBIGNEY	DATE 20-05-05	ANALYSE Y TAB. FAM. Y PRO/E Y LANGAGE E
VERIFIE G.PINON	DATE 04/10/2007	
APPROUVE L.KUBAT	DATE 04/10/2007	REPLACE
 C&K Components	 PROJECTION TER. DREIRE ECHELLE 2	DESIGNATION CCM01-2012LFT 2x4 contacts thru-hole switch NO 2 pegs
	BP 359 - 39105 Dole - FRANCE - TAILLE A3 FEUILLE 1 / 1	NUMERO CU 030288Y2012



PRODUCT SPECIFICATION

CCM01-MKII V2 - LFT


Ref. / PS-CCM01-MKII- 2

Page 1 / 8

ISSUE 1 – Rev. G: SEPTEMBER 2008

Approvals:

Laurent Kubat
Engineering Manager

 Date
16/09/08

Guillaume Pinon
Project Manager

Daniel Pequegot
Laboratory Manager

Jerome Smolinski
Product Manager

Jérôme Brochot
Quality Director

Note

This specification, attached documents and attached drawings cannot be communicated to anybody without written agreement of C&K.

Revision record:

Revision	Date	Comments
Issue 1	April 25 th , 2005	Creation
Issue 1 – Rev. A	Sept. 29 th , 2005	Update : <ul style="list-style-type: none">• Card end travel switch : dust sealed• Soldering processes : recommendation for solder thickness• Marking resistance (According to DCR N°D2000398)
Issue 1 – Rev. B	March 28 th , 2006	Update : <ul style="list-style-type: none">• Tab page 4 : Versions covered by this spec.• Option : I/O Protect diagram added (page 4)• §10 “Additional data” added (According to ECR -327)
Issue 1 – Rev. C	June 19 th , 2006	Update : <ul style="list-style-type: none">• Tab page 4 : Reinforced versions added• Static load test updated - § 7• Metallic peg retention test added - § 7• Operating Life test updated - § 8 (According to ECR -515)
Issue 1 – Rev. D	January 12 th , 2007	Update : <ul style="list-style-type: none">• Operating environment : Operating life – Recommendation updated• Additional data : Automatic assembly – Pick & Place note added. (According to ECR -742)
Issue 1 – Rev. E	August 8 th , 2007	Update : <ul style="list-style-type: none">• Solder heat resistance : 10s instead of 5s (LF version)• Resistance to fluids : comment added (according to ECR 1186)
Issue 1 – Rev. F	October 2 nd , 2007	Update : <ul style="list-style-type: none">• Recommendations of use added (§ 2). (according to ECR 1429)
Issue 1 – Rev. G	September 8 th , 2008	Update : <ul style="list-style-type: none">• UL data suppressed (according to ECR 2324) <ul style="list-style-type: none">• Reference of test specifications updated (according to ECR 2446)

SUMMARY

Preliminary / versions covered by this specification

- 1. Description**
- 2. Recommendation of use**
- 3. Physical data**
- 4. Using temperatures**
- 5. Electrical data**
- 6. Mechanical data**
- 7. Storage and handling environment**
- 8. Process environment**
- 9. Operating environment**
- 10. Applicable norms**
- 11. Additional Data**
- 12. Qualification Plan**

VERSIONS COVERED BY THIS SPECIFICATION

Reference	Drawing N°	Version type	Terminal Type	Housing type
CCM01-2012LFT	CU 030288Y2012	Standard version	Thru-hole	2 Pegs
CCM01-2013LFT	CU 030288Y2013	Standard version	SMT	2 Pegs
CCM01-2019LFT	CU 030288Y2019	I/O Protect version (see below diagram 1)	SMT	2 Pegs
CCM01-2027LFT	CU 030288Y2027	Reinforced version	SMT	4 metallic Pegs
CCM01-2031LFT	CU 030288Y2031	Reinforced version	SMT	2 metallic Pegs in diagonal

Note: Reference CCM01-XXXXLFT: Lead Free Tin


Option: I/O Protect

Diagram 1

1 - Description


Product group : CCM01

Product Sub Family : Mk2

Card type : Full-sized card

Contact type : Friction

Contact plating : Precious metal inlay

Contacts number : 8

Terminal type : SMT or thru-hole
see table page 4

Card end travel switch :
Switch NO: Normally Open
Dust sealed switch

Housing type : see table page 4

Generic specification (C&K) :
Proc. essai 20

2 - Recommendations of use

According to C&K recommendations: RU-CCM-001 document

3 - Physical data

Mass	5.0 g ± 1.0
Dimensions & lay out	According to drawing : see table page 4

4 - Using temperatures

Operating temperatures	- 40 °C / + 85 °C
Storage temperatures	- 40 °C / + 85 °C
Soldering temperature	According to IEC 61760-1 :2006

5 - Electrical data

Voltage / ct	≤ 5 Vdc
Current / ct	≤ 10 Ma
Contact resistance	≤ 100 mΩ
Voltage proof	≥ 750 Vrms
Insulation resistance	Initial measurement ≥ 1000 MΩ (100 VDC) After damp heat ≥ 1 MΩ recovery time : 4 hours After damp heat ≥ 200 MΩ recovery time : 24 hours

Card end travel switch characteristics :

- Max power	0.2 VA
- Max voltage	30 Vdc
- Min/Max current	50 μA min / 10 mA max
- Bounces	≤ 3 ms
- Voltage proof	≥ 750Vrms between signal contact / switch contacts ≥ 250Vrms between open contacts of the switch
- Insulation resistance	Initial measurement ≥ 1000 MΩ (100 VDC) After damp heat ≥ 1 MΩ recovery time : 4 hours After damp heat ≥ 200 MΩ recovery time : 24 hours between signal contact / switch contacts & between open contacts of the switch
- Contact resistance	≤ 100 mΩ

Card end travel switch sequence According to drawing : see table page 4

6 - Mechanical data

Card insertion force	10 N max
Card withdrawal force	1 N min / 10 N max
Contact force (signal contact)	According to drawing : see table page 4
Contact force (end travel switch)	0.8 N max to activate the switch 1.8 N max for complete actuator depression
Snap-in force (version with clips)	10 N min / 50 N max
Snap-off force (version with clips)	10 N min

7 - Storage and handling environment

Marking & Traceability	Designation : 20xxT (for CCM01-20xxLFT) Date code : year / week / day
Packaging conditions	According to drawing : CU 030278Y0043
Transport conditions	Sea-air-land / World wide / High ≤ 5 m 30°C / 85% HR According to H00-060

8 - Process environment

Soldering processes :

- Lead free reflow soldering process (*SMT terminals*)
 - According to IEC 61760-1:2006
Recommendation for solder paste thickness : ≥ 0.20 mm
- Lead Free single or double wave soldering process (*through Hole Terminals*)
 - According to IEC 61760-1:2006

Solder heat resistance	3 cycles at max profile according to IEC 61760-1:2006 According to IEC 60068-2-58
Static load (transverse) (CCM / PCB)	10 N / 1 mn / 4 directions (standard version) 40 N / 1 mn / 4 directions (reinforced version) According to IEC 512-5 test 8a/8b
Terminal robustness	1 bend / 45° / forward & back According to IEC 60068-2-21 test Ub method 1
Contact retention in insert	2 N / 10sec./ displacement < 0.3 mm According to IEC 512-8 test 15a
Metallic peg retention in housing <i>Reinforced version</i>	≥ 30 N (lateral & axial directions)
Solderability (wetting balance)	245°C According to IEC 60068-2-69
Dust sealed test (only for switch)	Dust test / IP5x According to IEC 60529:1989/A1:1999
Resistance to fluids	The product is not compatible with washing process.

9 – Operating environment

Operating life	$\geq 100\ 000$ cycles <ul style="list-style-type: none"> • at 10 N force for standard version • at 40 N force for reinforced version <i>Recommendation: 4 metal pegs. Other configurations are possible, according to customer integration.</i>
Vibration	10-500 Hz / 50 m/s ² / 3 axis / 2 hours per axis No discontinuity > 1 μ s According to IEC 60068-2-6.
Mechanical shock	500 m/s ² / ½ sinusoidal / 11 ms 3 shocks in the 2 directions of the 3 axis No discontinuity > 1 μ s According to IEC 60068-2-27.
Rapid change of temperature	100 cycles / - 40°C / + 85°C According to IEC60068-2-14, test Nb
Climatic sequence	Dry heat : 85°C / 16 hours Damp heat : 1 cycle 24 hours 55°C & 93% HR Cold : - 40°C / 2 hours Damp heat : 1 cycle 24 hours 55°C & 93% HR According to IEC 60068-2-61, test Z/ABDM
Dry heat storage	85°C / 250 hours According to IEC 60068-2-2 , test Bb.

Damp heat storage	40°C / 93% HR / 10 days According to IEC 60068-2-78 test Cab
Corrosion	96 hours / salt spray According to IEC 60068-2-11, test Ka.

The environmental tests can be cumulative according to the qualification file

10 - Applicable norms

Legal norm (EHS)	C&K procedure
Warranty period	1 year

11- Additional data

Free space under CCM	According to appendix 1
Automatic assembly - Pick & Place	Increase the diameter of holes on PCB to 3.4 mm \pm 0.05 to use standard version (plastic pegs). <i>However this assembly is not recommended. The best global life test performance will be achieved by using reinforced version (metal pegs), as mentioned above, see § 8, Operating life – recommendation (40 N insertion).</i>

12- Qualification Plan

According to Proc-20

Appendix 1

