





REVISION RECORD			
REV	ECO	DESCRIPTION	DATE
1		ADD PART NUMBER	28/05/11
2		DRAWING MODIFY	28/05/11



NOTES:

ELECTRICAL:

- 1. VOLTAGE RATING : 125 VAC RMS.
- 2. CURRENT RATING : 1.5 AMP.
- 3. CONTACT RESISTANCE : 100 MILLIOHMS MAX.
- 4. INSULATION RESISTANCE : 1000 MEGOHMS MIN @ 500 VDC.
- 5. DIELECTRIC STRENGTH : 750 VAC RMS 60Hz, 1MIN.

ENVIRONMENTAL:

- 1. STORAGE : -40°C TO +85°C.
- 2. OPERATION : 0°C TO 70°C.

CONFORM TO TIA/EIA 568 B.2-1
 MATES WITH MODULAR PLUG CONFORMING TO
 FCC PART 68, SUBPART F.

MECHANICAL:

- 1. HOUSING MATERIAL: PC UL94V-0
- 2. INSERT MATERIAL: PBT+20%GF UL94V-0
- 3. PCB MATERIAL: FR-4 THICKNESS: 1.6mm
- 4. CONTACT MATERIAL: PHOSPHOR BRONZE
- 5. ROHS COMPLIANT Δ STAMP PIN T=0.35mm

		DATE: 28/05/2008 CHECKED: [Signature] DESIGNED: [Signature] APPROVED: [Signature]	ASSMANN Electronics TITLE: A-TA3535-R (CAT6)
DWG NO.: PART NO. SEE NOTE	SCALE: 1:1	DO NOT SCALE DRAWING	SHEET X OF Y A3 2

8 | 7 | 6 | 5 | 4 | 3 | 2 | 1