



- MATERIAL: HOUSING-HIGH TEMPERATURE NYLON, BLACK, IR COMPATIBLE, UL 94V-0.
 TERMINALS - 0.33 [.013] THICK PHOS BRONZE PLATED WITH 1.27µm [.000050] MINIMUM HARD GOLD IN LOCALIZED AREA AND 3.81µm [.000150] MINIMUM TIN IN SOLDER AREA OVER 1.27µm [.000050] MINIMUM NICKEL UNDERPLATE.
 SHIELDS - 0.25 [.010] THICK COPPER ALLOY PLATED WITH 1.27 µm [.000050] MINIMUM NICKEL AND 2.03 µm [.000080] MINIMUM HOT TIN DIP ON PCB GROUND TABS.
- ⚠ JACK CAVITY CONFORMS TO FCC RULES AND REGULATIONS, PART 68 SUBPART F.
- ⚠ CAUTION: CATEGORY 5 JACK SOLDER TAIL POSITIONS DO NOT FOLLOW SAME NUMBER SEQUENCE AS THAT OF THE TRADITIONAL JACKS.



5558505-1
 PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		REVISED ECH-10-00487	DATE	11-16-08	BY	KS	CHK	SY	APP	
INCHES	MM	108-1163-2	REVISED ECH-10-00487	DATE	11-16-08	BY	KS	CHK	SY	APP
REV	DATE	DESCRIPTION	BY	CHK	APP					
AA	00									
CZ		REVISED ECH-10-00487								
SEE NOTE 1	SEE NOTE 1	CUSTOMER DRAWING	DATE	11-16-08	BY	KS	CHK	SY	APP	