



Notes:

1. Electrical Specifications:
 - Meets EIA/TIA-568-B.2 Cat.5e Specification
 - Contact Resistance: 20mOhm max.
 - Insulation Resistance: 500MOhm min. @ 100 VDC
 - Current Rating: 1.2A max. at 25°C
 - Working Voltage: 100 VDC
 - DWV: 1000 VDC/60s Contact to Contact, 1500 VDC/60s Contact to Metal Shell
 - Operating Temperature: -40°C to +85°C
2. Material and Finish:
 - Receptacle Housing: Polyester (Black) or Metallized ABS (Nickel Plated); UL94 V-0
 - Panel Nut: Brass, Finish: Nickel Plated
 - Panel Gasket: Silicone, Color: White
 - RJ45 IDC Jack Metal Shell: Copper Alloy, Nickel Plated
 - RJ45 IDC Jack Plastic Housing: Glass filled PBT UL94 V-0, Color: Black
 - RJ45 IDC Jack Contacts: Phosphor Bronze, Finish: 50u" Gold min. over Nickel
3. Connector can be front or rear mounted to a maximum panel thickness of 3.2mm.
4. RoHS compliant

Directive 2002/95/EC
"RoHS"
Compliant

Description	Part Number
Plastic Version	17-10015
Metallized Plastic Version	17-10016
Potted Plastic Version	17-10033
Potted Metallized Plastic Version	17-10034

THIS DRAWING AND ANY REVISIONS ARE THE PROPERTY OF CONEC. IT IS TO BE USED ONLY FOR THE PROJECT AND PARTS IDENTIFIED HEREON. IT IS NOT TO BE REPRODUCED, COPIED, OR TRANSMITTED IN ANY MANNER, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT THE WRITTEN PERMISSION OF CONEC.	Customer:		Tolerance Unless otherwise specified			Scale: 1.5:1	Dim. in mm	
	Name	Title	Approval Date	0 PLC ±0.10 1 PLC ±0.38 2 PLC ±0.51 3 PLC ±0.10 ANGLES ±3°		Autodesk Inventor	Material: See Notes	
	2007	Date	Name	Title: Receptacle Assembly Kit Industrial Ethernet Connector (IP67) with Cat. 5e RJ45 IDC Jack			Drawing No.: 39K1A332	DIN A3
	Draw.	Oct 25	Vincent Ke	Part No.: SEE P/N ABOVE			Sheet 1/1	
	Appd.	Oct 25	J. Chaudry					
Norm								
D-old								
b	origin	Jan/28/08	Vincent Ke					
a								
Rev.	Changes	Date	Name					