



- NOTES:
1. MATERIAL: SEE TABLE
 2. FINISHES: SEE TABLE
 3. PRODUCT SPECIFICATION: SEE SPECS
 4. PACKAGING: AS REQUIRED
 5. MATES WITH INDUSTRY STANDARD
 6. FORMERLY SD-84702-0006
 7. WIRING POLARIZATION & SEQUENCE PER EIA 568B.
 8. COMPATIBLE WITH SOLID AND STRANDED COPPER CONDUCTORS.
 9. CONDUCTOR RANGES ARE 22-26AWG WITH A MAX OF 7 STRANDS PER CONDUCTOR BUNDLE. LIMITING O.D. IS 0.55"
 10. CAN BE RETERMINATED UP TO 200 TIMES.

ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH
8	2	STUFFER CAP (MPN #201-345)	THERMOPLASTIC	WHITE
7	1	PUNCHDOWN BLOCK	THERMOPLASTIC	WHITE
6	1	PUNCHDOWN BLOCK	THERMOPLASTIC	WHITE
5	1	PCB	FR-4	GREEN
4	1	PANEL GASKET	NEOPRENE	BLACK
3	1	RJ-45 JACK W/PCB MTG	POLYESTER	BLACK
2	1	LOCK NUT	POLYESTER	BLACK
1	1	RECEPTACLE HOUSING	POYESTER	BLACK

ADDED NOTES 8.9.10
 EC NO: ETC2006-0183
 DRAWN BY: S. GILBERT
 CHECKED BY: R. KEMP
 APPROVED BY: GHR

QUALITY SYMBOLS
 ▽=0
 ▽=0

GENERAL TOLERANCES (UNLESS SPECIFIED)	
	INCH
4 PLACES	± .005
3 PLACES	± .01
2 PLACES	± .013
1 PLACE	± .015
ANGULAR ± 2°	

DIMENSION STYLE: IN/MM
 DRAWN BY: S. GILBERT
 CHECKED BY: R. KEMP
 APPROVED BY: GHR
 DATE: 03/07/30
 DATE: 03/08/04
 DATE: 03/08/04
 MATERIAL NO.: 847020006
 SIZE: B

SCALE: 4:1
 DESIGN UNITS: INCH
 THIRD ANGLE PROJECTION
 TITLE: PANEL MTG. RECEPTACLE RJ-45 PUNCHDOWN C/C INDUSTRIAL ETHERNET
 MOLEX INCORPORATED
 DOCUMENT NO.: SD-84702-004
 SHEET NO.: 1 OF 1
 THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION