


- △ BARREL TERMINAL WIRE RANGE: 19-28 AWG SOLID OR STRANDED WIRE. MAXIMUM INSULATION DIAMETER IS 1.65 [.065].
- 2. MOUNTING PANEL THICKNESS: 1.57 [.062] NOMINAL.
- △ MATERIALS: 8 POSITION STUFFER CAP - POLYCARBONATE, NATURAL.
DISCRETE STUFFER CAP - NYLON 6/6.
BARREL TERMINAL - TIN COATED PHOSPHOR BRONZE.
CONTACTS - NICKEL PLATED HIGH STRENGTH COPPER ALLOY HAVING SELECTIVE GOLD PLATING ON CONTACT AREA AND SELECTIVE TIN PLATING ON BARREL TERMINAL AREA.
HOUSING AND KEYSTONE - THERMOPLASTIC, 94 V-0 RATED. SEE TABLE FOR COLORS.
- 4. STUFFER CAPS SHIPPED NOT ASSEMBLED.
- 5. BARREL TERMINALS WILL ACCOMMODATE ONE OR TWO WIRES OF THE SAME TYPE AND WITHIN PLUS OR MINUS ONE WIRE GAUGE SIZE.
- △ KIT BULK PACKAGED 200 PER CARTON.



ELECTRICAL SCHEMATIC

OBsolete	Color	Wire Range	Description	Part No.
OBsolete	BLACK	22-28 AWG	KIT WITH 1 EIGHT POSITION STUFFER CAP	5-554578-5
OBsolete	LIGHT ALMOND	22-28 AWG	KIT WITH 1 EIGHT POSITION STUFFER CAP	5-554578-4
OBsolete	NATURAL	22-28 AWG	KIT WITH 8 DISCRETE STUFFER CAPS	5-554578-2
OBsolete	BLACK	22-28 AWG	KIT WITH 1 EIGHT POSITION STUFFER CAP	5-554578-1
OBsolete	LIGHT ALMOND	22-28 AWG	KIT WITH 1 EIGHT POSITION STUFFER CAP	554578-4
OBsolete	BLACK	22-28 AWG	KIT WITH 8 DISCRETE STUFFER CAPS	554578-2
OBsolete	BLACK	22-28 AWG	KIT WITH 1 EIGHT POSITION STUFFER CAP	554578-1

THIS DRAWING IS A CONTROLLED DOCUMENT. UNLESS OTHERWISE SPECIFIED, THE DIMENSIONS ARE IN INCHES. THE DIMENSIONS IN PARENTHESES ARE IN MILLIMETERS. THE DIMENSIONS IN SQUARE BRACKETS ARE IN INCHES. THE DIMENSIONS IN PARENTHESES ARE IN MILLIMETERS.

TE Connectivity
KEYSTONE JACK KIT, 8 POSITION, COMMERCIAL

REV	DATE	DESCRIPTION	BY	CHK	APP
00					
01					
02					
03					
04					
05					
06					
07					
08					
09					
10					

SIZE: A1 DATE: 00779 DRAWING NO: 554578

CUSTOMER DRAWING