



- NOTES:**
- ELECTRICAL:**
- VOLTAGE RATING : 125 VAC RMS.
 - CURRENT RATING : 1.5 AMP.
 - CONTACT RESISTANCE : 30 MILLIOHMS MAX.
 - INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 500 VDC.
 - DIELECTRIC STRENGTH : 1000 VAC RMS 60Hz, 1MIN.
 - LED RATINGS: FORWARD VOLTAGE: 2.2 VOLTS TYPICAL.
REVERSE VOLTAGE: 5 VOLTS MAXIMUM.
 - OPERATING: 750 CYCLES MIN.
- MECHANICAL:**
- HOUSING MATERIAL : NYLON UL94V-0. COLOR-BLACK.
 - INSERT MATERIAL : NYLON UL94V-0. COLOR-BLACK.
 - BACK PLATE MATERIAL : COLOR-BLACK.
 - LED SIZE : 3.2*2.0*7.0*1*2.54mm.
 - SHIELD MATERIAL : COPPER ALLOY 0.25mm THICKNESS PLATING NICKEL.
 - CONTACT MATERIAL : PHOSPHOR BRONZE 0.35mm THICKNESS
 - PLATING : SELECTIVE GOLD PLATING OVER NICKEL.
 - PCB RETENTION PRE-SOLDER : 1 LB MIN.
 - PCB RETENTION POST-SOLDER: 10 LBS MIN.
- ENVIRONMENTAL:**
- STORAGE : -40°C TO +85°C.
 - OPERATION : -40°C TO +85°C.
 - WAVE SOLDERING TEMPERATURE: 255~265°C(5~10 SECONDS)
 - RoHS COMPLIANT.
- MATES WITH MODULAR PLUG CONFORMING TO
FCC PART 68, SUBPART F.
UL FILE NO. E163191

PART NUMBER	LED COLOR		TAB TYPE	GOLD PLATING
	LED 1	LED 2		
E5J88-41LJ25-L	GREEN/YELLOW	GREEN/YELLOW	NO TAB	50u"
E5J88-W4LJ22-L	RED/GREEN	RED/GREEN	TOP & SIDE	6u"

TITLED RJ45 SIDE ENTRY LED JACK			
DRTO Cathy DATE 08/17/06		DRAWING NO. CE5J3069-LA /PART NO. SEE TABLE	
SCALE : 3:1		DO NOT SCALE DRAWING	
SHEET 1 OF 1		SIZE REV A3 0	

8 | 7 | 6 | 5 | 4 | 3 | 2 | 1

H
G
F
E
D
C
B
A