


PC Board Layout t=1.6mm
Component Side Shown Tolerance±0.05mm



- NOTES:**
- ELECTRICAL:**
- VOLTAGE RATING : 125 VAC RMS.
 - CURRENT RATING : 1.5 AMP.
 - CONTACT RESISTANCE : 50 MILLIOHMS MAX.
 - INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 500 VDC.
 - DIELECTRIC STRENGTH : 1000 VAC RMS 60Hz, 1MIN.
- MECHANICAL:**
- HOUSING MATERIAL : NYLON, UL94V-0.
 - CONTACT MATERIAL : PHOSPHOR BRONZE Ø0.46mm.
 - PLATING : GOLD PLATING OVER NICKEL.
 - OPERATING LIFE : 750 CYCLES MIN.
 - PCB RETENTION PRE-SOLDER : 1 LB MIN.
 - PCB RETENTION POST-SOLDER: 10 LBS MIN.
 - LED COLOR : OPTION
- ENVIRONMENTAL:**
- STORAGE : -40°C TO +85°C.
 - OPERATION: -40°C TO +85°C.
 - WAVE SOLDERING TEMPERATURE: 255~265°C(5~10 SECONDS)
 - RoHS COMPLIANT.
- MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.

PART NUMBER	LED COLOR		GOLD PLATING
	LED 1	LED 2	
E5J88-A4L3F2-L	GREEN	GREEN	6u"
E5J88-A4L3F4-L	GREEN	GREEN	30u"
E5J88-B4L3F2-L	GREEN	ORANGE	6u"
E5J88-C4L3F2-L	GREEN	YELLOW	6u"
E5J88-C4L3F4-L	GREEN	YELLOW	30u"

		FULL RISE ELECTRONIC CO., LTD	
RoHS Compliant		TITLE RJ45 LED JACK, 2x1PORTS	
DFTO Jeri Chi DATE 07/13/2006		DRAWING NO. CE5J3021-LA-01	
SCALE : 5:3		/PART NO. SEE TABLE	
DO NOT SCALE DRAWING		SHEET 1 OF 1	

8 | 7 | 6 | 5 | 4 | 3 | 2 | 1

H
G
F
E
D
C
B
A