A1RFRD10

REVISION RECORD				
REV	ECO	DESCRIPTION	DRFT	CHKD
1		ADD P/N	JAMY 12/10/'05	





PC Board Layout Component Side Shown

Thickness=1.6mm

ROHS PART NUMBER: E5908-XVCXXX-L

1- 3u" 2- 6u" 3-15u" 4-30u" 5-50u"

2-W/ TOP TABS
3-W/ SIDE TABS
4-W/ TOP&SIDE TABS
5-W/ TOP&BOTTOM&SIDE TABS

14-FRONT 4.57 W/O LOGO ⚠1
1J-FRONT 4.57 W/FRE LOGO W/O UL LOGO

NOTES:

ELECTRICAL:
1. VOLTAGE RATING : 125 VAC RMS.
2. CURRENT RATING : 1.5 AMP.
3. CONTACT RESISTANCE : 50 MILLIOHMS MAX.
4. INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 500 VDC.
5. DIELECTRIC STRENGTH : 1000 VAC RMS 60Hz, 1MIN.

MECHANICAL:
1. HOUSING&IIN'S& MATERIAL : PBT+30%.G.F BK UL94V-0.
2. CONTACT MATERIAL : PHOSPHOR BRONZE, t=0.35mm.
3. SHIELD MATERIAL : COPPER ALLOY, t=0.25mm.
4. PLATING : GOLD PLATING OVER NICKEL.
5. OPERATING LIFE : 750 CYCLES MIN.
6. PCB RETENTION PRE-SOLDER : 1 LB MIN.
7. PCB RETENTION POST-SOLDER: 10 LBS MIN.

ENVIRONMENTAL:
1. STORAGE : -40°C TO +85°C.
2. OPERATION: -0°C TO 70°C.
3. WAVE SOLDERING TEMPERRATURE: 230°C ~250°C (3~5 SECONDS).

MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.
CUL FILE NO. E163191

MM (INCH)	DFTD CY	DATE 06/11/05	FULL RISE ELECTRONIC CO., LTD
TOLERANCES EXCEPT AS NOTED	CHKD YHM	DATE 2005/12/12	
MM .0 ±0.2 .00 ±0.15 .000 ±0.075	MFD	DATE	TITLE STAMPED PIN III STACKED GANGED JACK, 2X4
ANGLES ± 0.5	APPVL LUSHENG	DATE 2005/12/12	
THIRD ANGLE PROJECTION	MATERIAL :		DRAWING NO. GE593B51-LC /PART NO. SEE NOTE
DETACHED LISTS	QT'Y :		SIZE A3 REV 1
	FINISH :		
	SCALE : 1.5 : 1		DO NOT SCALE DRAWING SHEET 1 OF 1

Downloaded from Elcodis.com electronic components distributor