



- NOTES:**
- ELECTRICAL:**
- VOLTAGE RATING : 125 VAC RMS.
  - CURRENT RATING : 1.5 AMP.
  - CONTACT RESISTANCE : 35 MILLIOHMS MAX.
  - INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 500 VDC.
  - DIELECTRIC STRENGTH : 1000 VAC RMS 60Hz, 1MIN.
- MECHANICAL:**
- HOUSING MATERIAL : GLASS FILLED NYLON UL94V-0.
  - CONTACT MATERIAL : PHOSPHOR BRONZE 0.46mm
  - CONTACT PLATING : GOLD PLATING OVER NICKLE
  - SHIELD PLATING : NICKEL PLATING OVER BRASS
  - OPERATING LIFE : 750 CYCLES MIN.
  - PCB RETENTION PRE-SOLDER : 1 LB MIN.
  - PCB RETENTION POST-SOLDER: 10 LBS MIN.
  - LED COLOR : LEFT- GREEN, RIGHT- YELLOW.
- ENVIRONMENTAL:**
- STORAGE TEMPERATURE : -40°C TO +85°C.
  - OPERATION TEMPERATURE: -40°C TO +85°C.
  - WAVE SOLDERING TEMPERATURE: 255~265°(5~10 SECONDS)
  - RoHS COMPLIANT.
- MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.

PART NUMBER
E5J88-C4B3F2-L

TITLE <b>STACKED GANGED JACK 2*3 PORTS</b>			
DFTD Cathy DATE 2006/09/11		DRAWING NO. CE5J3035-LA /PART NO. SEE TABLE	
SCALE : 5:3 		SHEET 1 OF 1	
DETAILED LIST TOLERANCES EXCEPT AS NOTED .0 ± 0.2 ± .00 ± 0.15 ± .000 ± 0.075 ± ANGLES ± 0.5		SIZE REV A3 0	

8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 | A