



Notes:

- Electrical Specifications:
 - Meets EIA/TIA-568-B.2 Cat.5e Specification
 - Contact Resistance: 20mOhm max.
 - Insulation Resistance: 500MOhm min. @ 100 VDC
 - Current Rating: 1.2A max. at 25° C
 - Working Voltage: 100 VDC
 - DWV: 1000 VDC/60s Contact to Contact, 1500 VDC/60s Contact to Metal Shell
 - Operating Temperature: -40° C to +85° C
- Material and Finish:
 - Receptacle Housing, Metal Cover, Panel Nut: Brass, Nickel Plated
 - Ball Chain: Copper Alloy, Nickel Plated
 - Panel Gasket: Silicone, Color: White
 - Cover Gasket: Silicone, Color: White
 - RJ45 PCB Jack Metal Shell: Copper Alloy, Nickel Plated
 - RJ45 PCB Jack Plastic Housing: Glass filled PBT UL94 V-0, Color: Black
 - RJ45 PCB Jack Contacts: Phosphor Bronze, Finish: 50u" Gold min. over Nickel
- Connector can be front or rear mounted to a maximum panel thickness of 3.2mm.
- RoHS compliant

Directive 2002/95/EC
"RoHS"
Compliant

Description	Part Number
Metal Version Receptacle + Cover with Shielded RJ45 PCB Jack	17-101654
Potted Metal Version Receptacle + Cover with Shielded RJ45 PCB Jack	17-101674

THIS DRAWING AND THESE DIMENSIONS ARE PRELIMINARY IN ANY WAY AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT THE EXPRESS WRITTEN PERMISSION OF CONEC CORPORATION.	Customer:		Tolerance Unless otherwise specified		Scale: 1.2:1	Dim. in mm
	Name		0 F.L.C. ± 0.10 1 F.L.C. ± 0.38 2 F.L.C. ± 0.25 3 F.L.C. ± 0.10 ANGLES ± 3°			
	Draw.	Date	Name		Receptacle + Cover Assembly Kit with Cat. 5e RJ45 PCB Jack Metal Version	
	Appd.	Jun. 05	Vincent Ke			
	Norm	Jun. 05	J. Chaudry			
c	Apr/01/10	Vincent Ke	D-old	Drawing No.: 17K1A252	Part No.: SEE P/N TABLE	DIN A3 Sheet 1/1
b	Aug/26/09	Vincent ke				
a	original					
Rev.	Changes	Date	Name			