


DESCRIPTION: SHIELDED DUST CAPS




ATTENUATION EFFICIENCY:

FREQUENCY MHZ	ATTENUATION dB	FREQUENCY MHZ	ATTENUATION dB	FREQUENCY MHZ	ATTENUATION dB	FREQUENCY MHZ	ATTENUATION dB
0.1	125	4	100	150	90	700	68
0.2	127	6	90	200	100	800	56
0.4	122	15	90	250	82	900	58
0.6	123	40	87	300	71	1000	52
1	120	60	82	400	70		
2	118	100	87	600	67		

"X XX" IN PART NUMBER
 POSITION (09, 15, 25)
 GENDER: 1 = MALE (BLUE)
 2 = FEMALE (RED)

MATERIAL: ABS WITH 50 MICRON GRAPHITE COATING

 NorComp	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OF SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.		DRAWN: PAM JENKINS	DATE: 10-9-00
			CHECKED:	DATE:
		SCALE:	SHEET 1 OF 1	REV 1
		DWG NO. 160-020-XXX-000		