



- △ MATERIAL: HOUSING—POLYCARBONATE, CLEAR
TERMINAL—.014 THICK PHOSPHOR BRONZE, PLATED WITH 1.27 μ m [.000050] MINIMUM THICK GOLD IN LOCALIZED GOLD PLATE AREA, GOLD FLASH OVER THE REMAINDER, OVER 2.54 μ m [.000100] MINIMUM THICK NICKEL UNDERPLATE.
- 2. ALL DIMENSIONS SHOWN ARE MAXIMUM UNLESS OTHERWISE SPECIFIED.
- 3. PLUG WILL ACCEPT 0.737[.029] - 0.99[.039] DIAMETER STRANDED WIRE, 26 OR 28 AWG WITH A 4.57 [.180] DIAMETER JACKET.
- △ TERMINATED DIMENSION 6.15 [.242] MAXIMUM.
- △ LATCH SHALL BE IN POSITION SHOWN IN DETAIL A AFTER CRIMPING.
- △ 500 ASSEMBLIES PER PACKAGE.
- △ 100 ASSEMBLIES PER PACKAGE.



△	5-555177-3
△	5-555177-2
PACKAGED	PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.		DN L. HALL 28MAR2008	TE Connectivity
DIMENSIONS: INCHES (MILLIMETERS)		OK S. MCNEILL 31MAR2008	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APP S. MCNEILL 31MAR2008	
Ø	PLC	±	
□	PLC	±	
□	PLC	±	
□	PLC	±	
□	PLC	±	
ANGLE		±	
MATERIAL	FINISH	WEIGHT	RESTRICTED TO
△	△		
CUSTOMER DRAWING		SIZE A2	CAGE CODE 00779
		DRAWING NO 555177	REV H1
		SCALE 4:1	SHEET 1 of 1

1471-9 (3/11)