



LIC		DST		REVISIONS			
HM	00	P	LM	DESCRIPTION	DATE	DM	APD
		H		REV. ECO-08-020668	27AUG08	GG	BM

- ⚠ DIMENSIONS ARE MAXIMUM UNLESS OTHERWISE SPECIFIED.
- ⚠ MATERIAL: HOUSING-POLYCARBONATE, CLEAR TERMINAL- PHOSPHOR BRONZE, PLATED WITH 1.27 μ m [.000050] MINIMUM THICK GOLD IN LOCALIZED GOLD PLATE AREA, GOLD FLASH OVER THE REMAINDER, OVER 2.54 μ m [.000100] MINIMUM THICK NICKEL UNDERPLATE.
- 3. PLUG WILL ACCEPT 24 OR 26 AWG SOLID WIRE, ϕ 0.99 [.039] MAXIMUM INSULATION DIAMETER, WITH A 4.96 [.195] DIAMETER MAXIMUM JACKET.
- ⚠ TERMINATED DIMENSION 6.15 [.242] MAXIMUM.
- ⚠ 500 ASSEMBLIES PER PACKAGE.
- ⚠ 100 ASSEMBLIES PER PACKAGE.

⚠	5-555426-3
⚠	5-555426-2
PACKAGED	PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.		DR	S. SIMPSON	11-10-93	Tyco Electronics Corporation Harrisburg, PA 17105-3608	
DIMENSIONS: mm (INCHES)		CHK	C. WHITT	11-18-93	PART NO	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APD	LAUBER/MCCREATH	11-23-93	MODULAR PLUG ASSEMBLY, 6 POSITION, LONG BODY, SOLID WIRE	
0 P/PC	±	APL	108-1163	SIZE	A2	00779C=555426
1 P/PC	±	APL	114-6016	SCALE	4:1	SHEET 1 of 1
2 P/PC	±	APL		REV	H	
3 P/PC	±	APL				
MATERIAL	FINISH	WEIGHT	CUSTOMER DRAWING			

AMP 1471-9 REV 31MAR2000

B55426

A