



KEYING OPTIONS  
 SOME DETAIL OMITTED FOR CLARITY

△ HOUSING: NYLON MOLDING COMPOUND, BLACK.  
 TERMINALS: 0.3(.012) THICK PHOS BRONZE.  
 PLATING: NICKEL UNDERPLATE OVER ENTIRE TERMINAL. 2.54µm(.000100) MINIMUM THICKNESS.  
 LOCALIZED PLATING AREA: 0.254µm(.000100) THICK GOLD OVER 1.016µm(.000400) MINIMUM THICK PALLADIUM NICKEL (OVER 0.051µm(.000002) MINIMUM THICK GOLD WHEN REQUIRED BY PROCESS CONDITIONS).

2. 558666-1 KEY1 (CLOSED) AS SHOWN.

KEY	PART NUMBER
KEY 5	558666-5
KEY 4	558666-4
KEY 3	558666-3
KEY 2	558666-2
KEY 1	558666-1
DESCRIPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DATE: 10/31/90	REV: 23	AMPI Incorporated Harrisburg, PA 17105-3608
SYMBOLS:	UNLESS OTHERWISE SPECIFIED:	UNIT: INCHES	SCALE: AS SHOWN	DESCRIPTION: CONNECTOR ASSEMBLY, CABLE, 15 POSITION, INFOPORT, SERIES III
FINISH:	FINISH:	FINISH:	FINISH:	REV: ONE ONE (PREVIOUS TO 4500)
DATE: 10/31/90	DATE: 10/31/90	DATE: 10/31/90	DATE: 10/31/90	REV: 23
DESIGNED BY: [Signature]	CHECKED BY: [Signature]	APPROVED BY: [Signature]	CUSTOMER DRAWING: A100778	REV: 23