www.schurter.com/pg07

0721-PS

FL° 🕃 🔣 16 ແ)

IEC Appliance Inlet C8, Snap-in Mounting, Front Side, Solder Terminal





Description

- Panel Mount:
- Snap-in version, from front side
- Appliance Inlet, Pin temperature 70 °C, Protection class II - Solder terminals

Approvals

- UL File Number: E96454 CSA File Number: 73165


Technical Data


Ratings IEC	2.5 A / 250 VAC; 50 Hz
Ratings UL/CSA	2.5 A / 250 VAC; 60 Hz
Dielectric Strength	> 2 kVAC between L-N (1 min/50 Hz)
Allowable Operation Temp.	-25 °C to 70 °C
Degree of Protection	from front side IP 40 acc. to IEC 60529
Protection Class	Suitable for appliances with protection class 2 acc. to IEC 61140
Terminal	Solder terminals
Panel Thickness s	Snap-in from 0.8 - 1.6 mm
Material: Housing	Thermoplastic, black, UL 94V-0

Dimensions

0721-PS







Solder terminals for wires

Variants Type	Panel mounting	Panel Thickness s [mm]	Terminal	Order Number
0721-PS	Snap-in	0.8 - 1.6	Solder terminals	4300.0098
Packaging unit	50 Pcs			



Downloaded from Elcodis.com electronic components distributor



RoHS

General Product Information, Approvals, RoHS, CHINA-RoHS, Mating Connectors, e-Store, SCHURTER-Stock-Check, Distributor-Stock-Check, Accessories

Appliance Inlet	C8 acc. to IEC/EN 60320-1,
	UL 498, CSA C22.2 no. 42 (for cold
	conditions) pin-temperature 70 °C,
	2.5 A, Protection Class 2



1

Mating Outlets/Connectors

Category / Description

Power CordOverview complete



Power Cord with IEC Connector C7, Straight 70°C	2510
Power Cord with IEC Connector C7, Angled	2511
Power Cord with IEC Plug C7, Angled	2514
Power Cord with IEC Connector C7, Straight 70°C	4810

Power Cordfurther types to0721-PS

Power Supply or Interconnection CordOverview complete



Divers Power Supply and Interconnection Cords 2.5 A	CS01.0121.150
Divers Power Supply and Interconnection Cords 2.5 A	CS01.0221.150
Divers Power Supply and Interconnection Cords 2.5 A	CS01.0321.150
Divers Power Supply and Interconnection Cords 2.5 A	CS01.0421.150
Divers Power Supply and Interconnection Cords 2.5 A	CS03.0421.150
Power Supply or Interconnection Cordfurther types to0721-PS	

