

## IEC Appliance Inlet C14 with Shielding, "Lock and Shield" Mounting



GRF2: only with shield, without line filter

**Description**

- Panel Mount:
- Snap-in version from rear-side
- 2 Functions:
- Appliance Inlet Protection class I, with EMC-shield

**Approvals**

- VDE Certificate Number: 40025743
- UL File Number: E96454
- CSA File Number: 38456

**Characteristics**

- Time saving "Lock and Shield" snap-in design for rear-panel mounting
- All single elements are already wired
- Innovative EMC-shielding with flexible steel segments for an excellent contact to the panel
- Qualified for use in equipment according IEC/EN 60950

**Other versions on request**

- With solder terminals

**References**

Alternative: version with line filter

**Weblinks**

[General Product Information](#), [Approvals](#), [RoHS](#), [CHINA-RoHS](#), [Mating Connectors](#), [e-Store](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#), [Accessories](#)


**Technical Data**

Ratings IEC	10A @ Ta 40 °C / 250VAC; 50Hz
Ratings UL/CSA	15A @ Ta 40 °C / 125VAC; 60Hz
Dielectric Strength	> 1.7 kVDC between L-N
	> 2.7 kVDC between L/N-PE
	Test voltage (2 sec)
Allowable Operation Temp.	-25 °C to 85 °C
Climatic Category	25/085/21 acc. to IEC 60068-1
Degree of Protection	from front side IP 40 acc. to IEC 60529
Protection Class	Suitable for appliances with protection class 1 acc. to IEC 61140
Terminal	Quick connect terminals 4.8 x 0.8 mm
	Plug Connector
	Solder terminal on request
Panel Thickness s	Snap-in: 1.2/1.5/2 mm
Material: Housing	Thermoplastic, black, UL 94V-0


Appliance-Inlet/-Outlet	C14 acc. to IEC/EN 60320-1, UL 498, CSA C22.2 no. 42 (for cold conditions) pin-temperature 70 °C, 10A, Protection Class 1
MTBF	> 3'300'000h acc. to MIL-HB-217 F

**Dimensions**


GRF2



1) Terminal for earth screw M4




1) Terminal for earth screw M4



This area must be conductive for optimal shielding. Do not apply paint or coatings.

### Dimensions

Step 1




Place the socket in top edge of the panel cut-out.

Step 2




Push the socket upwards.

Step 3



Push the socket forward into the panel cut-out.

Step 4



Release the socket. The component is self adjusting.

### Variants

Rated Current IEC [A]	Rated Current UL [A]	Filter-Type	Panel Thickness s [mm]	Additional ground terminal	Order Number
10	15	without	1.2	-	GRF2.0212.11
10	15	without	1.5	-	GRF2.0215.11
10	15	without	2	-	GRF2.0220.11
10	15	without	1.2	Quick connect terminal 4.8 x 0.8	GRF2.0312.11
10	15	without	1.5	Quick connect terminal 4.8 x 0.8	GRF2.0315.11
10	15	without	2	Quick connect terminal 4.8 x 0.8	GRF2.0320.11

Packaging unit 100 Pcs

### Mating Outlets/Connectors

#### Category / Description

#### Appliance Outlet Overview complete



IEC Appliance Outlet F, Screw-on Mounting, Front Side, Solder Terminal	4787
IEC Appliance Outlet F, Snap-in Mounting, Front Side, Solder or Quick-connect Terminal	4788
IEC Appliance Outlet F or H, Screw-on Mounting, Front Side, Solder, PCB or Quick-connect Terminal	5091
IEC Appliance Outlet F or H, Screw-on Mounting, Front Side, Solder or Quick-connect Terminal	5092

#### Appliance Outlet further types to GRF2

#### Connector Overview complete



IEC Connector C15, Rewireable, Straight	0101
IEC Connector C15A, Rewireable, Straight	0102
IEC Connector C15A, Rewireable, Straight	0102-G
IEC Connector C15A, Rewireable, Angled	0112
IEC Connector C13, Rewireable, Angled	4012

#### Connector further types to GRF2

#### Power Cord Overview complete



Power Cord with IEC Connector C13, Angled	0311
Power Cord with IEC Connector C13, Angled	3011
Power Cord with IEC Connector C13, Angled	3012
Power Cord with IEC Connector C13, Angled	3013
Power Cord with IEC Connector C13	3020

#### Power Cord further types to GRF2

