


- △ CONTACTS DESIGNED FOR 28 AWG STRANDED OR 26, 28, & 30 AWG SOLID WIRE.
- △ AMP TRADEMARK LOCATED IN APPROX AREA SHOWN.
- △ STANDOFFS: POSN 8 (2) STANDOFFS AS SHOWN. POSN 14-20 (3) STANDOFFS, (1) CENTERED BETWEEN (2) SHOWN
- △ .000100-.000200 BRIGHT TIN LEAD OVER .000050 NICKEL ON ENTIRE CONTACT.
- △ HEIGHT AFTER TERMINATION IS .253 REF.
- △ INDICATES NO 1 POSITION.
- △ MATERIAL:
 MOLDED PARTS: 94V-0 RATED THERMOPLASTIC, COLOR BLACK.
 CONTACTS: PHOSPHOR BRONZE



OBSOLETE	.900	9	1.088	.900	.950	19	20	746613-5
OBSOLETE	.800	8	.988	.800	.850	17	18	746613-4
OBSOLETE	.700	7	.888	.700	.750	15	16	746613-3
OBSOLETE	.600	6	.788	.600	.650	13	14	746613-2
OBSOLETE	.300	3	.488	.300	.350	7	8	746613-1
	F	E	D	C	B	A	NO OF POSN	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT. DATE: 11-08-88 BY: J. BEACHEY 11-08-88
 SPRAGUE ELECTRONICS CORPORATION
 HARRISBURG, PA 17105-3008

REVISIONS: 114-40013 (REVISED)
 114-40005 (REVISED)
 KIT, AMP-LATCH DIP PLUG, ASSEMBLED .100 X .300 CENTERS, FULL TIN PLATED CONTACTS
 CUSTOMER DRAWING
 DATE: 10-11 1 1 G1