THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION -.-.-
© COPYRIGHT - BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST
GP	00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	B	REVISED PER ECO-09-003886	06APR2009	CJV	CWR

1. HOUSING & COVER: POLYESTER, BLACK, UL 94V-0 RATED.
2. CONTACTS: PHOSPHOR BRONZE.
3. CONTACTS: 1.27µm[.000005] MIN GOLD ON RIBBON CABLE TERMINATION AREA 2.54µm[.000100] MIN MATTE TIN ON SOLDER TAILS, ALL OVER 1.27µm[.000050] MIN NICKEL.
4. CONTACTS WILL ACCEPT 28 AWG STRANDED OR 26, 28, 30 AWG SOLID WIRE.
5. HEIGHT AFTER TERMINATION IS 6.43[.253].





RECOMMENDED HOLE LAYOUT







NO OF STANDOFFS	D	C	B	A	NO OF POSN	PART NO
10	31	85.85 [3.380]	78.74 [3.100]	63	64	1-5111852-2
9	29	80.77 [3.180]	73.66 [2.900]	59	60	1-5111852-1
8	24	68.07 [2.680]	60.96 [2.400]	49	50	1-5111852-0
7	21	60.45 [2.380]	53.34 [2.100]	43	44	5111852-9
7	19	55.37 [2.180]	48.26 [1.900]	39	40	5111852-8
6	16	47.75 [1.880]	40.64 [1.600]	33	34	5111852-7
4	12	37.59 [1.480]	30.48 [1.200]	25	26	5111852-6
4	9	29.97 [1.180]	22.86 [0.900]	19	20	5111852-4
3	7	24.89 [0.980]	17.78 [0.700]	15	16	5111852-3
3	6	22.35 [0.880]	15.24 [0.600]	13	14	5111852-2
2	4	17.27 [0.680]	10.16 [0.400]	9	10	5111852-1

THIS DRAWING IS A CONTROLLED DOCUMENT.

TYP C. ATTADIA - DOCSO 11-26-24
CHK C. ROHDE 11-26-24
APVD M. WALMSLEY 11-26-24

Tyco Electronics Corporation
Harrisburg, PA 17105-3608

DIMENSIONS: mm [INCHES]
TOLERANCES UNLESS SPECIFIED: 0 PLC ± -, 1 PLC ± -, 2 PLC ± 0.13 [.005], 3 PLC ± -, 4 PLC ± -, ANGLES ± -
MATERIAL
FINISH
WEIGHT -

NAME: PLUG ASSEMBLY, DIP, AMP-LATCH
PRODUCT SPEC: 108-40013
APPLICATION SPEC: 114-40005

SIZE A1 | CAGE CODE 00779 | DRAWING NO C-5111852 | RESTRICTED TO -

CUSTOMER DRAWING | SCALE 10:1 | SHEET 1 OF 1 | REV B

Downloaded from Elcodis.com electronic components distributor