



- NOTES:
1. CRIMP ACCEPTS 22 TO 26 GA. WIRE WITH (1.65)±.065 MAX INSULATION DIA.
 2. DIMENSIONS GIVEN ACROSS CENTERLINES ARE SYMMETRICAL ABOUT THOSE CENTERLINES WITHIN HALF THE TOTAL TOLERANCE.
 3. OPTIONAL DESIGN (.86±.05)±.034±.002
 4. TERMINAL CONFORMS TO PRODUCT SPEC. 08-50.
 5. CAT EAR OPTION TO BE USED WITH 41695 HOUSING ONLY.

MATERIAL CODE 2578 * * * * *

WINDING SPEC.
A=PER ES-339-A
BLANK=PER ES-339-B
L=LOOSE

PLATING CODE
(PER SDES-88)
*(P909) OVERALL HOT TIN DIP: 2.54 MICROMETERS MIN
(550) SELECT GOLD: 0.38 MICROMETERS MIN.
OVERALL GOLD FLASH: 0.05 MICROMETERS MIN.
OVERALL NICKEL UNDERPLATE: 0.76 MICROMETERS MIN.
(555) SELECT GOLD: 0.38 MICROMETERS MIN.
OVERALL NICKEL UNDERPLATE: 0.76 MICROMETERS MIN.

OPTIONS
BLANK=AS SHOWN
I=WITH CAT EARS
2=LOW INSERTION FORCE

*THE PRIMARY SHIPPING CARTON WILL BE LABELED "COMPLIANT TO ROHS DIRECTIVE 2002/95/EC AND ELV ANNEX II OF DIRECTIVE 2000/53/EC." CARTONS WITHOUT THIS LABEL MAY CONTAIN PRODUCT WITH TIN-LEAD PLATING.

ENTER DESCRIPTION EC NO. IEP2005-0928 DRN/BR/IN/OL 2004/11/16 CHK/OS/AN/EC 2004/11/02 APPROVED FOR RELEASE W	QUALITY SYMBOLS 	GENERAL TOLERANCES (UNLESS SPECIFIED) mm INCH		DRAWN BY: PEREZ/AR DATE: 01/29/87	TITLE: CRIMP TERMINAL (3.96)±.156 CENTERS 22 TO 26 GA WIRE	SCALE: INCH DESIGN UNITS: INCH	THIRD ANGLE PROJECTION
		4 PLACES ±.005 3 PLACES ±.010 2 PLACES ±.025 1 PLACE ±.036	±.005 ±.010 ±.025 ±.036	CHECKED BY: PATEL DATE: 01/29/87	APPROVED BY: LENZ DATE: 01/29/87	MATERIAL NO.: SD-2578 DOCUMENT NO.: SD-2578	MOLEX INCORPORATED
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE CHART		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			

