



REDRAWN IN ME-10 EC NO: UCP2006-3071 DRAWN: JOMERC1 2006/06/22 CHK'D: JOMERC1 2006/06/22 APPR: JOMERC1 2006/06/23	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE IN/MM	SCALE 8:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	
	$\nabla=0$ $\nabla=0$	4 PLACES ± --- ± --- 3 PLACES ± --- ± .010 2 PLACES ± 0.25 ± .016 1 PLACE ± 0.40 ± --- ANGULAR ±1/2°	DRAWN BY R/JF DATE 1/17/92 CHECKED BY DATE 1/17/92 APPROVED BY RAS DATE 1/17/92	TITLE	MALE CRIMP TERMINAL, 12, 10 & 8AWG MINIFIT SR.		
	DESCRIPTION	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	MATERIAL NO. SEE CHART	DOCUMENT NO. SD-42817-*	MOLEX INCORPORATED		
	REV H1		SIZE C	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			

tb_frame_C_P_ME_T
Rev. D 2004/04/02

	13	12	11	10	9	8	7	6	5	4	3	2	1
ITEM NUMBER	WIRE RANGE	DIM. A	DIM. B	DIM. C	DIM. D	DIM. E	DIM. F	DIM. G	MAX. INSULATION DIAMETER	PLATING			
42817-0011	12 & 10 AWG	.213±.024 (5.40±.60)	.240±.016 (6.10±.40)	.067 (1.70)	.232±.024 (5.90±.60)	.260±.016 (6.60±.40)	.087 (2.20)	1.087 (27.60)	.209 (5.30)	OVERALL TIN			
42817-0031	8 AWG	.229±.024 (5.83±.60)	.292±.016 (7.42±.40)	.067 (1.70)	.236±.024 (6.00±.60)	.216±.016 (5.50±.40)	.087 (2.20)	1.087 (27.60)	.260 (6.60)	OVERALL TIN			
42817-0111	12 & 10 AWG	.213±.024 (5.40±.60)	.240±.016 (6.10±.40)	.067 (1.70)	.232±.024 (5.90±.60)	.260±.016 (6.60±.40)	.087 (2.20)	1.165 (29.60)	.209 (5.30)	OVERALL TIN			
42817-0131	8 AWG	.229±.024 (5.83±.60)	.292±.016 (7.42±.40)	.067 (1.70)	.236±.024 (6.00±.60)	.216±.016 (5.50±.40)	.087 (2.20)	1.165 (29.60)	.260 (6.60)	OVERALL TIN			
42817-0012	12 & 10 AWG	.213±.024 (5.40±.60)	.240±.016 (6.10±.40)	.067 (1.70)	.232±.024 (5.90±.60)	.260±.016 (6.60±.40)	.087 (2.20)	1.087 (27.60)	.209 (5.30)	SELECT GOLD			
42817-0032	8 AWG	.229±.024 (5.83±.60)	.292±.016 (7.42±.40)	.067 (1.70)	.236±.024 (6.00±.60)	.216±.016 (5.50±.40)	.087 (2.20)	1.087 (27.60)	.260 (6.60)	SELECT GOLD			
42817-0112	12 & 10 AWG	.213±.024 (5.40±.60)	.240±.016 (6.10±.40)	.067 (1.70)	.232±.024 (5.90±.60)	.260±.016 (6.60±.40)	.087 (2.20)	1.165 (29.60)	.209 (5.30)	SELECT GOLD			
42817-0132	8 AWG	.229±.024 (5.83±.60)	.292±.016 (7.42±.40)	.067 (1.70)	.236±.024 (6.00±.60)	.216±.016 (5.50±.40)	.087 (2.20)	1.165 (29.60)	.260 (6.60)	SELECT GOLD			

NOTES:

- 1) MATERIAL: COPPER ALLOY 151, .020/(.50) THICK.
- 2) PLATING:

1 = .000100/(.00254) MIN. *TIN OVER
.000050/(.00127) MIN. NICKEL.

2 = .000030/(.00076) MIN. SELECT GOLD IN CONTACT AREA.
.000100/(.00254) MIN. SELECT *TIN ON SOLDER TAILS
OVER .000050/(.00127) MIN. NICKEL.

* THE PRIMARY SHIPPING CARTON WILL BE LABELED
"COMPLIANT TO ROHS DIRECTIVE 2002/95/EC
AND ELV ANNEX II OF DIRECTIVE 2000/53/EC."
CARTONS WITHOUT THIS LABEL MAY CONTAIN
PRODUCT WITH TIN-LEAD.

1D) WHEN USING OVERALL TIN PLATED TERMINALS,
FOR APPLICATIONS INVOLVING VIBRATION AND/OR THERMAL CYCLING,
MOLEX STRONGLY RECOMMENDS THE USE OF NYE LUBRICANT, NYOGEL 760G,
ON THE MATING AREA OF THE TERMINAL. LUBRICANT SHOULD BE APPLIED
AFTER THE TERMINALS ARE INSERTED INTO THE HOUSING.

12) THE 8AWG TERMINAL WILL ALSO ACCOMMODATE 2 12AWG WIRES
SEE CRIMP SPEC FOR DETAILS.

13) CRIMP SPECS.:
638210000 FOR 10AWG & 12AWG
638300000 FOR 8AWG, 8AWG HI-FLEX & DOUBLE 12AWG

- 3) PRODUCT SPEC.: PS-42815-001
- 4) PART IS DESIGNED IN METRIC.
- 5) TERMINALS FOR USE WITH STRANDED WIRE ONLY.
- 6) ITEM NUMBERS PRECEDED BY AN 'X' IN THE CHART ARE NOT AVAILABLE.
- 7) THE 8 AWG TERMINAL HAS NO INSULATION CRIMP. THE SECONDARY
CRIMP SECTION ACTS AS A STRAIN RELIEF ON THE BARE CONDUCTOR ONLY.
SEE MOLEX CRIMP SPECIFICATION FOR DETAILS.

8) AFTER CRIMPING, THIS DIMENSION IS .140/(3.55) MINIMUM.

9) AFTER CRIMPING, THIS DIMENSION IS .089/(2.25) MAXIMUM.

10) WHEN USING THE 8 AWG TERMINAL WITH 'HI-FLEX' WIRE, MOLEX STRONGLY
RECOMMENDS THAT THE APPROPRIATELY RATED HEAT SHRINK INSULATION BE
APPLIED OVER THE WIRE INSULATION AND CRIMP AREA, AS SHOWN, TO MINIMIZE
WIRE INSULATION CREEPAGE OUTSIDE OF HOUSING.

SEE SHEET 1 EC NO: UCP2006-3071 DRWN: JOMERC1 2006/06/22 CHKD: JOMERC1 2006/06/22 APPR: JOMERC1 2006/06/23 REV	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE IN/MM	SCALE ---	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION
	▽=0	4 PLACES ± --- ± ---	DRAWN BY SEP	DATE 1/10/95	TITLE	
	▽=0	3 PLACES ± --- ± .010	CHECKED BY RJP	DATE 1/10/95	MALE CRIMP TERMINAL 10-12 AWG AND 8 AWG MINIFIT SR. SERIES	
		2 PLACES ± 0.25 ± .016	APPROVED BY RAS	DATE 1/10/95	MOLEX MOLEX INCORPORATED	
	1 PLACE ± 0.40 ± ---	ANGULAR ±1/2°	MATERIAL NO.	DOCUMENT NO.	SHEET NO.	
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	SEE CHART	SD-42817-*	2 OF 2	
			THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			