



- 1) ADATTO PER GOMMINO AMP P/N 281934-... (SUITABLE FOR SINGLE WIRE SEAL AMP P/N 281934-...)
- 2) MASSIMA CORRENTE 14A. (MAX. CURRENT 14A)

PRE STAGNATO (PRE-TINNED)	BRONZO FOSFOROSO (PH. BRONZE)	282466-1
FINITURA / COLORE (FINISH / COLOUR)	MATERIALE (MATERIAL)	NUMERO (PART NUMBER)

CUSTOMER DWG. FOR REFERENCE ONLY DISEGNO PER CLIENTE SOLO PER RIFERIMENTO

THIS DRAWING IS UNPUBLISHED RELEASE FOR PUBLICATION 1990

© COPYRIGHT 1990 BY AMP INCORPORATED, HARRISBURG, PA. ALL INTERNATIONAL RIGHT RESERVED. AMP PRODUCTS MAY BE COVERED BY U.S. AND FOREIGN PATENT AND/OR PATENT PENDING

TOLLERANZE, SE NON DIVERSAMENTE SPECIFICATO (TOLERANCES, UNLESS OTHERWISE SPECIFIED)	DIAM. ISOLANTE (INS. DIA. RANGE) VED. NOTA 1) (SEE NOTE 1))	RANGO FILO (WIRE RANGE)	SCALA (SCALE)
± 0.3		1.5-2.5mm ²	5:1
ANGOLI (ANGLES) ± 2°	tyco Electronics AMP ITALIA S.p.A. Corso F.lli Cervi, 15 COLLEGNO (TORINO)		

REV.	REVISIONI (REVISION RECORD)	DIS. DATA (DR) (DATE)	APP. (APP.)
A2	REVISED FOR ET00-0024-04 M.G. 2004	12 APR '92	BERTINI
A1	REVISED FOR ET00-0072-98 M.P. '98	12 DEC '92	A. BRUNI
A	RELEASED FOR PROD. (EC. 133-93) C.P. 16 NOV '93		

DESCRIZIONE (DESCRIPTION)	LOC. SIZE NUMERO (DWG NO)	REV.	FOGLIO (SHEET)
MINI MIC SRS REC. CONTACT	I A4 C-282466	A2	1 DI (OF) 1