



- △ MATERIAL:
 RECEPTACLE CONTACTS— PHOSPHOR BRONZE
 RECEPTACLE HOUSING AND TERMINATING COVERS— THERMOPLASTIC,
 COLOR: BLACK.
- △ PLATING:
 RECEPTACLE CONTACTS— 0.00076 [0.00030] MINIMUM GOLD PLATE IN CONTACT AREA,
 0.00127 [0.00050] MINIMUM BRIGHT TIN-LEAD PLATE IN TERMINATION AREA,
 ALL OVER 0.00127 [0.00050] MINIMUM NICKEL.
- 3 RECOMMENDED WIRE:
 28 AWG— 0.91 [0.36] MAX O.D. PVC OR POLYETHYLENE INSULATION.
- 4 SHORT—LONG CONTACT SEQUENCE MUST ALTERNATE BUT MAY BEGIN WITH EITHER
 A SHORT OR LONG CONTACT.
- △ PLATING:
 RECEPTACLE CONTACTS— 0.00076 [0.00030] MINIMUM GOLD PLATE IN CONTACT AREA,
 0.00127 [0.00050] MINIMUM MATTE TIN PLATE IN TERMINATION AREA,
 ALL OVER 0.00127 [0.00050] MINIMUM NICKEL.
- △ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

REV	DATE	DESCRIPTION	BY	CHK	APP
OBSOLETE	△	71.83 63.91 62.23 [2.828] [2.516] [2.450]	49	100	6-104892-0-
OBSOLETE	△	65.48 57.56 55.88 [2.578] [2.266] [2.200]	44	90	5-104892-9-
△		59.13 51.21 49.53 [2.328] [2.016] [1.950]	39	80	5-104892-8
△		52.78 44.86 43.18 [2.078] [1.766] [1.700]	34	70	5-104892-7
OBSOLETE	△	46.43 38.51 36.83 [1.828] [1.516] [1.450]	29	60	5-104892-6-
△		40.08 32.16 30.48 [1.578] [1.266] [1.200]	24	50	5-104892-5
△		33.73 25.81 24.13 [1.328] [1.016] [0.950]	19	40	5-104892-4
△		27.38 19.46 17.78 [1.078] [0.766] [0.700]	14	30	5-104892-3
△		21.03 13.11 11.43 [0.828] [0.516] [0.450]	9	20	5-104892-2
OBSOLETE	△	14.68 6.76 5.08 [0.578] [0.266] [0.200]	4	10	5-104892-1
OBSOLETE	△	71.83 63.91 62.23 [2.828] [2.516] [2.450]	49	100	1-104892-0-
OBSOLETE	△	65.48 57.56 55.88 [2.578] [2.266] [2.200]	44	90	104892-9
OBSOLETE	△	59.13 51.21 49.53 [2.328] [2.016] [1.950]	39	80	104892-8
△		52.78 44.86 43.18 [2.078] [1.766] [1.700]	34	70	104892-7
OBSOLETE	△	46.43 38.51 36.83 [1.828] [1.516] [1.450]	29	60	104892-6-
△		40.08 32.16 30.48 [1.578] [1.266] [1.200]	24	50	104892-5
△		33.73 25.81 24.13 [1.328] [1.016] [0.950]	19	40	104892-4
△		27.38 19.46 17.78 [1.078] [0.766] [0.700]	14	30	104892-3
△		21.03 13.11 11.43 [0.828] [0.516] [0.450]	9	20	104892-2
OBSOLETE	△	14.68 6.76 5.08 [0.578] [0.266] [0.200]	4	10	104892-1

THIS DRAWING IS A CONTROLLED DOCUMENT. (REV) (DESCRIPTION) (DATE)

TE Connectivity

REV	DATE	DESCRIPTION	BY	CHK	APP
AD	00	REVISED PER EDD-11-004820			

AMP/ODDU 50/50 GRID CABLE CONN. ASSY WITH LATCH

108-1443

114-7010

00779G=104892

CUSTOMER DRAWING