



- △ NYLON, UL 94-V0 RATED, RED.
- △ PHOSPHOR BRONZE.
- △ 3.81um [.000150] MIN TIN-LEAD OVER 1.27um [.000050] MIN NICKEL.
- △ 0.76um [.000030] MIN GOLD FOR A LENGTH OF 4.95 [.195] MIN FROM MATING END 3.81um [.000150] MIN TIN-LEAD FOR A LENGTH OF 4.88 [.192] MIN ON OPPOSITE END, BOTH OVER 1.27um [.000050] MIN NICKEL.
- △ 3.81um [.000150] MIN TIN OVER 1.27um [.000050] MIN NICKEL.
- △ 0.76um [.000030] MIN GOLD FOR A LENGTH OF 4.95 [.195] MIN FROM MATING END 3.81um [.000150] MIN TIN FOR A LENGTH OF 4.88 [.192] MIN ON OPPOSITE END, BOTH OVER 1.27um [.000050] MIN NICKEL.

4.60 [-.181]	△	NO	1-207532-1
4.60 [-.181]	△	YES	1-207532-0
4.60 [-.181]	△	NO	207532-9
4.60 [-.181]	△	YES	207532-8
9.68 [-.381]	△	NO	207532-7
4.60 [-.181]	△	NO	207532-4
4.60 [-.181]	△	YES	207532-3
4.60 [-.181]	△	NO	207532-2
4.60 [-.181]	△	YES	207532-1

THIS DRAWING IS A CONTROLLED DOCUMENT		DATE: 02/04/20	REV: 0	BY: [Signature]	CHK: [Signature]	APP: [Signature]
DIMENSIONS: mm (INCH)		SYMBOLS: UNLESS NOTED	UNITS: mm	SCALE: 1:1	MATERIAL: HOUSING: 1	
CONTACT: SEE TABLE		FINISH: CONTACT		MOUNTING TABS		PART NO
CUSTOMER DRAWING		SEE: 00779	REV: 2	DATE: 01/11/20	REV: 2	REV: N