


| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A | 1 1/8-18NEF-2A |
| B | 19 |
| C | 4 |
| D | 34.2 |
| E | 25.4 |
| F | 27 |
| G | 35 |
| H | 3.1 |

| NO. | BESCHREIBUNG / DESCRIPTION |
|-----|---|
| 2 | ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET |
| 6 | KONTAKTBUCHSE / CONTACT SOCKET |
| 8 | DOSENGEHÄUSE / SHELL |



| |
|--|
| Note: Due to an automatic nomenclature system, numbers generated may not be sequential. |
| Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind. |
| Material Specification: |
| Shell Material: Aluminium alloy |
| Shell Plating: Olive drab chromate coating over cadmium plating |
| Insulator Material: Neoprene |
| Contact Material: Copper alloy |
| Contact Plating: Gold 0.5 µm; |

| | | | |
|---|-------------------------------|-------------|------------------------|
| all dimensions are in mm | | drawing for | |
| Dimensions without tolerance indications are general tolerances in acc. with DIN7168m | | CUSTOMER | |
| ITT <i>Engineered for life</i> <small>ITT CANON DIVISION</small> <small>© 1988 Westinghouse</small> | description CA3102E18-1S-A176 | | |
| | Box mounting receptacle | | |
| Solder Cup / Socket / Layout: 18-1 | | page 1/1 | revision 302.8, Feb 11 |
| <small>© All rights reserved. Reproduction or use in any form without written authorization of ITT Canon</small> | | | |