

	G max.
	1.65 <sub>-0.25</sub>
ØF max.	

NO.	MASSE / DIMENSIO
А	5/8-24UNEF-2A
в	9/16-24NEF-2A
с	14.2
D	2.8
Е	28.7
F	21.8
G	16.2

₿
•)

 
 Note:
 Due to an automatic nomenciature system, numbers generated may not be sequential.

 Notiz:
 Durch ein automatisches Benennungssystem können Numenferungen entstehen, die nicht Kortaufend sind.

Shell Material: Aluminium alloy Shell Material: Aluminium alloy Shell Plating: Olive drab chromate coating over cadmium platin Insulator Material: Neoprene Contact Material: Copper alloy

Material Specification:

Contact Plating: Hard silver

	all dimensions are in mm Dimensions without tolerance indications are general tolerances in acc. with DIN7168m			drawing for Bm CUSTOMER
g	Engineered for life	description CA3101E Cable connecting plug without Endbell AWG Crimp / Pin / Layor		4P-F80-F42 4
	© All rights reserved, Reproduction or whotever is only permitted with written ou			evision 02 8. Feb 11

NO.	BESCHREIBUNG / DESCRIPTION		
1	ISOLIERKÖRPER STIFT / INSULATOR PIN		
5	KONTAKTSTIFT/ CONTACT PIN		
8	DOSENGEHÄUSE / SHELL		