



| NO. | MASSE / DIMENSIO | | |
|-----|------------------|--|--|
| А | 5/8-24UNEF-2A | | |
| В | 9/16-24NEF-2A | | |
| С | 14.2 | | |
| D | 2.8 | | |
| Е | 28.7 | | |
| F | 21.8 | | |
| G | 16.2 | | |

| NO. | BESCHREIBUNG / DESCRIPTION | | |
|-----|---|--|--|
| 2 | ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET | | |
| 6 | KONTAKTBUCHSE / CONTACT SOCKET | | |
| 8 | DOSENGEHÄUSE / SHELL | | |



| Note: Due to an automatic nomenclature system, numbers generated may not be sequential. | | all dimensions are in mm | drawing for | |
|---|-----|---|--|-----------|
| Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind. | | Dimensions without tolerance indi | cations are general tolerances in acc. with DIN7168m | COSTONER |
| | 1 | l | description CA3101E10SL-4S | S-F42 |
| Material Specification: | 1 1 | Engineered for life ITI CANNON GmbH D - 71384 WeiszbaldGermany | Cable connecting plug without Endbell Solder Cup / Socket / Layout: 10SL-4 | |
| Shell Material: Aluminium alloy | | | | |
| Shell Plating: Olive drab chromate coating over cadmium plating | hg | | | |
| Insulator Material: Neoprene | 1 | | | |
| Contact Material: Copper alloy |] | © All rights reserved. Reproduction or issue to third in any form underver is only permitted with written authorization of ITT (annon 1/1 302 8, Feb 11 | | |
| Contact Plating: Hard silver | | whatever is only permitted with written authorization of ITT Cannon 1/1/1 302.8 | | 8. Feb 11 |