


		G max.
		1.65 _0.25
ØF max.	·	

NO.	MASSE / DIMENSIO
А	7/8-20UNEF-2A
в	3/4-20UNEF-2A
с	14.2
D	3.2
Е	28.7
F	28.2
G	22.5



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.	all dimensions are in mm Dimensions without tolerance indications are general tolerances in acc. with DIN7168m		
Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.	Dimensions without tolerance indications are general tolerances in acc. with DIN/168m		CUSTOMER
Nummenerangen einstenen, die nicht fordabiend and.	×>	description CA3101E14S-5P-	F42
Material Specification:	Cable connecting plug		
Shell Material: Aluminium alloy		without Endbell	
Shell Plating: Olive drab chromate coating over cadmium plating	Engineered for life		
Insulator Material: Neoprene	ITT CANNON GmbH D - 71384 Weinstadt/Germany	Solder Cup / Pin / Layout: 14S-5	
Contact Material: Copper alloy	© All rights reserved, Reproduction or issue to third in any form 🗾 🍈 page revision		
Contact Plating: Hard silver	© All rights reserved. Reproduction or issue to third in any form wholever is only penalted with written authorization of ITT Cannon		3. Feb 11

NO. BESC		BESCHREIBUNG / DESCRIPTION
	1	ISOLIERKÖRPER STIFT / INSULATOR PIN
	5	KONTAKTSTIFT/ CONTACT PIN
	8	DOSENGEHÄUSE / SHELL