

	G max.
-	1.65_0.25
ØF max.	

NO.	MASSE / DIMENSIO
А	7/8-20UNEF-2A
в	3/4-20UNEF-2A
с	14.2
D	3.2
Е	28.7
F	28.2
G	22.5

(C	A	
ĺ			

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.	all dimensions are in mm Dimensions without tolerance indications are general tolerances in acc. with DIN7168m		drawing for
Notiz: Durch ein automatisches Benennungssystem können			CUSTOMER
Nummerierungen entstehen, die nicht fortlaufend sind.		description CA3101E14S-1P-F42 Cable connecting plug	
Material Specification:	🗌 💙 ІТТ		
Shell Material: Aluminium alloy		without Endbell	
Shell Plating: Olive drab chromate coating over cadmium plating	Engineered for life		
Insulator Material: Neoprene	ITT CANNON GmbH D - 71384 Weinstadt/Germany	Solder Cup / Pin / Layout: 14S-1	
Contact Material: Copper alloy	© All rights reserved. Reproduction or issue to third in any form whatever is only penilited with written authorization of ITT Cannon 111 111 111 1111 1111 1111 11111 111111		
Contact Plating: Hard silver			3. Feb 11

NO.	BESCHREIBUNG / DESCRIPTION
1	ISOLIERKÖRPER STIFT / INSULATOR PIN
5	KONTAKTSTIFT/ CONTACT PIN
8	DOSENGEHÄUSE / SHELL