



| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A | 28.8 |
| B | 7/8-20UNEF-2B |
| C | 3/4-20UNEF-2A |
| D | 28.7 |

| NO. | BESCHREIBUNG / DESCRIPTION |
|-----|--------------------------------------|
| 1 | ISOLIERKÖRPER STIFT / INSULATOR PIN |
| 5 | KONTAKTSTIFT / CONTACT PIN |
| 7 | ZYLINDERGHÄUSE / BARREL |
| 9 | ÜBERWURFMUTTER / COUPLING NUT |
| 10 | DICHTRING FRONT / FRONT SEALING RING |



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.
 Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.

| Material Specification: | |
|-------------------------|--|
| Shell Material: | Aluminium alloy |
| Shell Plating: | Olive drab chromate coating over cadmium plating |
| Insulator Material: | Neoprene |
| Contact Material: | Copper alloy |
| Contact Plating: | Hard silver |

| all dimensions are in mm | | drawing for | |
|---|---|------------------------|--|
| Dimensions without tolerance indications are general tolerances in acc. with DIN7168m | | CUSTOMER | |
|  ITT Engineered for life <small>ITT CANADON GmbH 01-71504 WeiersheimGermany</small> | description CA3106E14S-6P-F42 | | |
| | Plug, straight without Endbell Solder Cup / Pin / Layout: 14S-6 | | |
| © All rights reserved. Reproduction or issue is forbidden in any form unless otherwise is only permitted with written authorization of ITT Cannon | page 1/1 | revision 302.8, Feb 11 | |