


NO.	MASSE / DIMENSION
A	24.1
B	5/8-24UNEF-2B
C	9/16-24NEF-2A
D	28.7

NO.	BESCHREIBUNG / DESCRIPTION
1	ISOLIERKÖRPER STIFT / INSULATOR PIN
5	KONTAKTSTIFT / CONTACT PIN
7	ZYLINDERGHÄUSE / BARREL
9	ÜBERWURFMUTTER / COUPLING NUT
10	DICHTRING FRONT / FRONT SEALING RING



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.

Material Specification:	
Shell Material:	Aluminium alloy
Shell Plating:	Olive drab chromate coating over cadmium plating
Insulator Material:	Neoprene
Contact Material:	Copper alloy
Contact Plating:	Hard silver

all dimensions are in mm  
 Dimensions without tolerance indications are general tolerances in acc. with DIN7168m  
 drawing for CUSTOMER

**ITT**  
 Engineered for life  
 ITT CANADIAN CORP.  
 617560, Wiesbaden, Germany

description CA3106E10SL-4P-F80-F42  
 Plug, straight  
 without Endbell  
 AWG Crimp / Pin / Layout: 10SL-4

© All rights reserved. Reproduction or issue is forbidden in any form  
 whenever it is not permitted with written authorization of ITT Cannon

page 1/1  
 revision 302.8, Feb 11