


| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 1 1/2-18NEF-2A    |
| B   | 20.6              |
| C   | 4                 |
| D   | 34.2              |
| E   | 35.3              |
| F   | 34.9              |
| G   | 44.5              |
| H   | 3.7               |

| NO. | BESCHREIBUNG / DESCRIPTION          |
|-----|-------------------------------------|
| 1   | ISOLIERKÖRPER STIFT / INSULATOR PIN |
| 5   | KONTAKTSTIFT / CONTACT PIN          |
| 8   | DOSENGEHÄUSE / SHELL                |



|  |
|--|
| Note: Due to an automatic nomenclature system, numbers generated may not be sequential.                      |
| Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind. |
| <b>Material Specification:</b>   |
| Shell Material: Aluminium alloy  |
| Shell Plating: Olive drab chromate coating over cadmium plating  |
| Insulator Material: Neoprene   |
| Contact Material: Copper alloy   |
| Contact Plating: Hard silver   |

|   |   |
|---|---|
| all dimensions are in mm<br>Dimensions without tolerance indications are general tolerances in acc. with DIN7168m | drawing for<br>CUSTOMER                             |
| <b>ITT</b><br><i>Engineered for life</i><br>ITT GANON GmbH<br>D-73249 Heimenkirch                                 | description MS3102E24-7P<br>Box mounting receptacle |
| © All rights reserved. Reproduction or issue to third in any form without written authorization of ITT Cannon     | Solder Cup / Pin / Layout: 24-7                     |
| page 1/1  | revision 302.8, Feb 11                              |