


NO.	MASSE / DIMENSION
A	37.4
B	1 1/4-18UNEF-2B
C	1 1/8-18NEF-2A
D	37.7

NO.	BESCHREIBUNG / DESCRIPTION
1	ISOLIERKÖRPER STIFT / INSULATOR PIN
5	KONTAKTSTIFT / CONTACT PIN
7	ZYLINDERGHÄUSE / BARREL
9	ÜBERWURFMUTTER / COUPLING NUT
10	DICHTRING FRONT / FRONT SEALING RING



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Note: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.

Material Specification:	
Shell Material:	Aluminium alloy
Shell Plating:	Olive drab chromate coating over cadmium plating
Insulator Material:	Neoprene
Contact Material:	Copper alloy
Contact Plating:	Hard silver

all dimensions are in mm  
 Dimensions without tolerance indications are general tolerances in acc. with DIN7168m  
 drawing for CUSTOMER

 <b>ITT</b> <i>Engineered for life</i> <small>ITT CANADON GmbH          01-71504 Weensriederweg</small>	description CA3106E20-4P-F42 Plug, straight without Endbell Solder Cup / Pin / Layout: 20-4
	© All rights reserved. Reproduction or issue to third in any form whatever is only permitted with written authorization of ITT Cannon page 1/1 revision 302.8, Feb 11