



| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 1 1/8-18NEF-2A    |
| B   | 19                |
| C   | 4                 |
| D   | 34.2              |
| E   | 25.4              |
| F   | 27                |
| G   | 35                |
| H   | 3.1               |

| NO. | BESCHREIBUNG / DESCRIPTION              |
|-----|---|
| 2   | ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET |
| 6   | KONTAKTBUCHSE / CONTACT SOCKET          |
| 8   | DOSENGEHÄUSE / SHELL                    |



|  |
|--|
| Note: Due to an automatic nomenclature system, numbers generated may not be sequential.                      |
| Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind. |
| Material Specification:  |
| Shell Material: Aluminium alloy  |
| Shell Plating: Olive drab chromate coating over cadmium plating  |
| Insulator Material: Neoprene   |
| Contact Material: Copper alloy   |
| Contact Plating: Hard silver   |

|  |  |                           |
|--|--|---------------------------|
| all dimensions are in mm<br>Dimensions without tolerance indications are general tolerances in acc. with DIN7168m  |  | drawing for<br>CUSTOMER   |
| <br><b>ITT</b><br><i>Engineered for life</i><br><small>ITT CANNON GROUP</small><br><small>© 1998 Westinghouse</small> | description<br>CA3102E18-9S-F80<br>Box mounting receptacle |                           |
|  | AWG Crimp / Socket / Layout: 18-9                          | page<br>1/1               |
| <small>© All rights reserved. Reproduction or issue is forbidden in any form without the written authorization of ITT Cannon</small>   |  | revision<br>302.8, Feb 11 |