



| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 1 1/4-18NEF-2A    |
| B   | 19                |
| C   | 4                 |
| D   | 34.2              |
| E   | 29                |
| F   | 29.4              |
| G   | 38                |
| H   | 3.1               |

| NO. | BESCHREIBUNG / DESCRIPTION          |
|-----|-------------------------------------|
| 1   | ISOLIERKÖRPER STIFT / INSULATOR PIN |
| 5   | KONTAKTSTIFT/ CONTACT PIN           |
| 8   | DOSENGEHÄUSE / SHELL                |



|  |
|--|
| Note: Due to an automatic nomenclature system, numbers generated may not be sequential.                      |
| Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind. |
| Material Specification:  |
| Shell Material: Aluminium alloy  |
| Shell Plating: Olive drab chromate coating over cadmium plating  |
| Insulator Material: Neoprene   |
| Contact Material: Copper alloy   |
| Contact Plating: Hard silver   |

|  |  |
|--|--|
| all dimensions are in mm<br>Dimensions without tolerance indications are general tolerances in acc. with DIN7168m  | drawing for<br>CUSTOMER  |
| <br><b>ITT</b><br><i>Engineered for life</i><br><small>ITT CANON GROUP<br/>31-1586 Westwood Parkway</small> | description CA3102E20-22PX-01<br>Box mounting receptacle<br>Metric Crimp / Pin / Layout: 20-22 |
| <small>© All rights reserved. Reproduction or issue in third in any form without prior written authorization of ITT Cannon.</small>  | page 1/1<br>revision 302 8. Feb 11   |