



	D max.				
NO.	BESCHREIBUNG / DESCRIPTION				
1	ISOLIERKÖRPER STIFT / INSULATOR PIN				
5	KONTAKTSTIFT/ CONTACT PIN				
8	DOSENGEHÄUSE / SHELL				



		_	
□ G ±0.3	4	NO.	MASSE / DIMENSIO
		А	1 1/2-18NEF-2A
□ F ±0.1		В	20.6
		С	4
1.65 _0.25		D	34.2
 - 0.23		Е	35.3
		F	34.9
		G	44.5
T T		н	3.7



ſ	Note: Due to an automatic nomenclature system, numbers generated may not be sequential.		all dimensions are in mm	drawing for		
Ī	Notiz: Durch ein automatisches Benennungssystem können		Dimensions without tolerance indi	ations are general tolerances in acc. with DIN7168m CUSTOMER		
L	Nummerierungen entstehen, die nicht fortlaufend sind.			description CA3102F24-5P		
	Material Specification:		V ITT	Box mounting receptacle		
Ī	Shell Material: Aluminium alloy			DOX mounting receptable		
	Shell Plating: Olive drab chromate coating over cadmium plating	ng	Engineered for life	0-14 0 (B)- (1+ 04.5		
	Insulator Material: Neoprene		ITT CANNON GribH D - 71384 Weinstadt/Germany	Solder Cup / Pin / Layout: 24-5		
	Contact Material: Copper alloy		© All rights reserved. Reproduction or issue to third in any tons subserver is only penalted with written authorization of ITT Curron 1/1/1 1/1/1 302.8. Feb 1.1			
	Contact Plating: Hard silver		whatever is only pennitted with written authorization of ITT Carnon 1/1 302 8. Feb 11			