


NO.	MASSE / DIMENSIO
Α	37.4
В	1 1/4-18UNEF-2B
С	1 1/8-18NEF-2A
D	37.7

NO	BESCHREIBUNG / DESCRIPTION			
1	ISOLIERKÖRPER STIFT / INSULATOR PIN			
5	KONTAKTSTIFT/ CONTACT PIN			
7	ZYLINDERGHÄUSE / BARREL			
9	ÜBERWURFMUTTER / COUPLING NUT			
10	DICHTRING FRONT / FRONT SEALING RING			



2 ±0.25

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.		all dimensions are in mm Dimensions without tolerance indications are general tolerances in acc.		
Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.		Dimensions without tolerance incl		
			description CA3106E	
Material Specification:		V ITT	Plug, straight	
Shell Material: Aluminium alloy			"	
Shell Plating: Olive drab chromate coating over cadmium plating	ng	Engineered for life	without Endbell	
Insulator Material: Neoprene		ITT CANNON GmbH D - 71384 Weinstadt/Germany	Solder Cup / Pin / Layou	
Contact Material: Copper alloy		© All rights reserved, Reproduction or issue to third in any form		
Contact Plating: Hard silver		wholever is only permitted with written or	ved, Reproduction or issue to third in any form emitted with written authorization of ITT Cannon	